View NSN Online: https://aerobasegroup.kr/nsn/6810-00-245-6695

EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV -- ETHYL ACETATE -- 6810-00-245-6695

Product ID:ETHYL ACETATE

MSDS Date: 10/03/1996

FSC:6810

NIIN:00-245-6695

MSDS Number: BDNFW === Responsible Party ===

Company Name: EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV

Address: EASTMAN RD

Box:511

City:KINGSPORT

State:TN ZIP:37662 Country:US

Info Phone Num:423-229-2000

Emergency Phon

e Num:HEALTH 800-EASTMAN; 800-424-9300

CAGE:7B604

=== Contractor Identification ===

Company Name: AMJAY CORP. DBA AMJAY CHEMICALS

Address:11200 WESTHEIMER SUITE 310

Box:218786 City:HOUSTON

State:TX

ZIP:77218-8786 Country:US

Phone:713-492-2000

CAGE:64184

Company Name: EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV

Address: EASTMAN RD

Box:511

City:KINGSPORT

State:TN ZIP:37662 Country:US

Phone:615-229-2000

CAGE:7B604

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL A

ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS
========== Hazards Identification ============
Effects of Overexposure:EYES-IRRITATION,SKIN-PROLONGED CONTACT DRIES & CRACKS.VAPOR IRRITATES MUCOUS MEMBRANES,NARCOTIC EFF.
======================================
First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES.CALL DOCTOR.SKIN-FLUSH WI
TH WATER.INHALATION-REMOVE TO FRESH AIR
======================================
Flash Point Method:TCC Flash Point:24.8F,-4.0C Lower Limits:2.02 Upper Limits:10.7 Extinguishing Media:WATER SPRAY,CARBON DIOXIDE,DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
=========== Accidental Release Measures ===========
Spill Release Procedures:CONTAIN SPILL,IF SMALL FLUSH WITH LARGE VOLUME OF WATER.REMOVE ANY SOURCE OF SPARK S OF FLAME.PROVIDE ADEQUATE EXHAUST.ABSORB MATERIAL
============ Handling and Storage ==============
Handling and Storage Precautions:AVOID EYE CONTACT.AVOID REPEATED OR PROLONGED SKIN CONTACT.USE WITH ADEQUATE VENTILATION TO KEEP BELOW TLV.KEEP CONTAINER CLOSED
====== Exposure Controls/Personal Protection =======
Respiratory Protection:SELF CONTAINED IF NEEDED,ESPECIALLY IN CONFINED AREAS Ventilation:LOCAL - RECOMMENDED Protective Gloves:RUB

CETATE (SARA III) CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 85% OSHA PEL:400 PPM

BER Eye Protection:FACE SHIELD/SAFETY GOGGLE Supplemental Safety and Health
======== Physical/Chemical Properties ===========
HCC:F3 Boiling Pt:B.P. Text:172F,78C Vapor Pres:75 Vapor Density:3.0 Spec Gravity:0.902 Evaporation Rate & DERATE Appearance and Odor:COLORLESS LIQUID WITH A SWEET ESTER ODOR.
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES OXI DIZERS

======= Disposal Considerations ===========

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE FOR SHIPPING TO DISPOSAL AREA

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. A ny person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.