View NSN Online: https://aerobasegroup.kr/nsn/8010-00-246-6443

HERCULITE PRODUCTS INC -- TURPENTINE (ASTM D-13) -- 8010-00-246-6443

Product ID:TURPENTINE (ASTM D-13) MSDS Date:01/01/1985 FSC:8010 NIIN:00-246-6443 MSDS Number: BDNJW === Responsible Party === Company Name: HERCULITE PRODUCTS INC Address:ABEERDEEN RD Box:467 City:EMIGSVILLE State:PA ZIP:17318 Country:US Info Phone Num:717-764-1191/FAX 717-764-5211 **Emergency Phon** e Num:717-764-1191/FAX 717-764-5211 CAGE:13324 === Contractor Identification === Company Name: HERCULES INCORPORATED Address:HERCULES PLAZA City:WILMINGTON State:DE ZIP:19894 Country:US Phone:302-594-5000 CAGE:28284 Company Name: HERCULITE PRODUCTS INC Address:1107 BROADWAY Box:467 **City:NEW YORK** State:NY ZIP:10010-2802 Country:US CAGE:13324

Ingred Name:SOLVENTS Fraction by Wt: 100% ACGIH TLV:100PPM

====== Hazar

Effects of Overexposure:MAY CAUSE EYE IRRITATION DERMITITAS OF SKIN,MAY CAUSE KIDNEY INFECTIONS.

First Aid:EYE:FLUSH W/WATER,CALL A DR.SKIN:WASH W/SOAP & WATER.INHAL:REMOVE TO FRESH AIR.IF SWALLOWED:DO NOT INDUCE VOMITING,

Flash Point:99F TCC 37 C Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2

Spill Release Procedures: ELIMINATE IGNITION SOURCE. STOP SPILL AT ONCE, CONTAIN SPILL BY DIKE, ETC. PUMP INTO SALVAGE TANK. AVOID CONTACT W/VAPOR OR SPRAY MIST.

Handling and Storage Precautions:NORMAL,KEEP AWAY FROM FLAMES OR HIGH HEAT.USE ONLY W/ADEQUATE VENTILATION.AVOID PROLONGED CONTACT W/SKIN.

Other Precautions: AVOID CONTACT W/OXIDIZING MATERIALS.

\_\_\_\_\_

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:AS NEEDED TO MAINTAIN CONCENTT BELOW TLV LEVEL Ventilation:LOC EXHAUST-RECOMMENDED Protective Gloves:RECOMMENDED Eye Protection:RECOMMENDED Supplemental Safety and Health PROCURED UNDER ASTM D-13

HCC:F3 Boiling Pt:B.P. Text:307 F 152 C Spec Gravity:.864 Evaporation Rate & amp; Reference:1 Solubility in Water:NEGLIGIBLE Appearance and Odor:SLI

## GHTLY YELLOW COLOR W/A PINACEOUS ODOR Percent Volatiles by Volume:99.0

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:STRONG OXIDIZING MATERIALS Conditions to Avoid Polymerization:CONTACT W/STRONG ACIDS FOR LEWIS ACIDS

Waste Disposal Methods:LIQUID INCINERATION.

Disclaimer (provided with this information by the compiling agenci es):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.