

BURNLEY BATTERY & MFG CO -- BURNLEY SOLDERING PASTE -- 3439-00-255-4566

=====
Product Identification
=====

Product ID: BURNLEY SOLDERING PASTE

MSDS Date: 05/06/1985

FSC: 3439

NIIN: 00-255-4566

MSDS Number: BDPCW

=== Responsible Party ===

Company Name: BURNLEY BATTERY & MFG CO

Address: 103 CLAY ST

Box: 511

City: NORTH EAST

State: PA

ZIP: 16428

Country: US

Info Phone Num: 814-725-3595

Emergency Phone Num: 814-7

25-3595

Preparer's Name: MICROBAC LABORATORIES INC

CAGE: 19530

=== Contractor Identification ===

Company Name: BURNLEY BATTERY AND MFG CO

Address: 103 CLAY ST

Box: 511

City: NORTH EAST

State: PA

ZIP: 16428-1537

Country: US

Phone: 814-725-3595

CAGE: 19530

=====
Composition/Information on Ingredients
=====

Ingred Name: ZINC CHLORIDE (SARA III)

CAS: 7646-85-7

RTECS #: ZH1400000

Fraction by Wt: 25.2%

OSHA PEL: 1 MG/M3/2 STEL

ACGIH TLV: 1 MG/M3/2 STEL FUME93

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000

LBS

Ingred Name:PETROLATUM

Fraction by Wt: 70.8%

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION:NAUSEA. EYE IRRITATION UPON CONTACT.

=====
First Aid Measures
=====

First Aid:EYE: IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL MD. INGESTION:DRINK WATER & CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:>356F,>180C

Extinguishing Media:DRY CHEMICAL OR CO*2.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:PASTE FORM STANDARD WIPING PROCEDURE.

=====
Handling and Storage
=====

Handling and Storage Precautions:NORMAL STORAGE.

=====
Exposure Controls/Personal Protection
=====

Ventilation:NORMAL ROOM VENTILATION (MFR).

Supplemental Safety and Health

PRODUCT CONFORMS TO FED SPEC O-F-506, TYPE 1, FORM A

=====
Physical/Chemical Properties
=====

HCC:N1

NRC/State Lic Num:NA

Boiling Pt:B.P. Text:165F,74C

Melt/Freeze Pt:M.P/F.P Text:153F,67C

Vapor Pres: