

MICHEL AND PELTON CO -- FOG OIL -- 9150-00-261-7895

=====  
Product Identification  
=====

Product ID:FOG OIL  
MSDS Date:01/01/1985  
FSC:9150  
NIIN:00-261-7895  
MSDS Number: BDPNW  
=== Responsible Party ===  
Company Name:MICHEL AND PELTON CO  
Address:5743 LANDREGAN ST  
City:EMERYVILLE  
State:CA  
ZIP:94608-2515  
Country:US  
Info Phone Num:COMPANY OUT OF BUSINESS  
Emergency Phone Num:COMPANY OUT OF BUSINESS  
CAGE:91  
341

==== Contractor Identification ===  
Company Name:MICHEL AND PELTON CO  
Address:5743 LANDREGAN ST  
Box:City:EMERYVILLE  
State:CA  
ZIP:94608-2515  
Country:US  
CAGE:91341

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM OIL  
Fraction by Wt: 100%

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL/INGEST:PUNG,SORE THROAT,COUGH,SHORTNESS  
OF BREATH,LABORED BRTHG; SKIN/EYES:CORR,RED,PAIN,BURNS

=====

=====  
First Aid Measures  
=====

First Aid:REMOVE TO FRESH AIR. GET MEDICAL ATTENTION. EYES, SKIN: FLUSH W. H\*2O REMOVE/ ISOLATE CONTAM CLOTHING. KEEP WARM & QUIET. GIVE CPR/OXYGEN IF NEED. STAY UPWIND. KEEP UNPROTECTED PERSONS AWAY FROM AREA .

=====  
Fire Fighting Measures  
=====

Flash Point:330F,COC  
Lower Limits:UNK  
Upper Limits:UNK  
Extinguishing Media:REGULAR FOAM,CO\*2,OR DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF-CNTND B RTHG APP  
Unusual Fire/Explosion Hazard:WILL BURN.CONTAINER MAY EXPLODE. VAPOR IS EXPLOSION HAZARD.FLAM VAPOR MAY SPREAD AWAY FROM SPILL.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER ABSORBENT MATERIAL.PREVENT RUNOFF TO SEWERS STREAM,OR OTHER BODIES OF WATER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WEAR SELF-CNTND BRTHG APP  
Ventilation:MECHANICAL (GENERAL/LOCAL EXHAUST)  
Protective Gloves:RUBBER  
Eye Protection:GOGGLES  
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.  
Supplemental Safety and Health  
SPEC TYPE SGF

=====  
Physical/Chemical Properties  
=====

HC

C:V6  
Spec Gravity:0.91  
Appearance and Odor:LIGHT YELLOW LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS, ACIDS AND ALKALIES.  
Stability Condition to Avoid:AVOID CONTACT WITH STRONG OXIDIZERS  
Hazardous Decomposition Products:MAY FORM TOXIC MATL. CO\*2, CO, VARIOUS  
HYDROCARBONS,ETC.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPO  
SAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.