View NSN Online: https://aerobasegroup.com/nsn/9150-00-261-8144

Product ID:VV-G-846A MSDS Date:08/01/1990 FSC:9150 NIIN:00-261-8144 **MSDS Number: BDPPN** === Responsible Party === Company Name:SULFLO INC. Address:1158 ERIE AVE. Box:285 **City:NORTH TONAWANDA** State:NY ZIP:14120-3507 Country:US Info Phone Num:716-695-3585 Emergency Phone Num:716-695-3585 Preparer's Name: THOMAS G.MUSILLI, **TECH.DIR** CAGE: JO986 === Contractor Identification === **Company Name:SULFLO INC** Address:1158 ERIE AVE Box:285 **City:NORTH TONAWANDA** State:NY ZIP:14120-3507 Country:US Phone:716-695-3585 CAGE:1V074 Company Name:SULFLO INC. Address:1158 ERIE AVE Box:285 City:NORTH TONAWANDA State:NY ZIP:14120-3507 Country:US Phone:716-695-3585 CAGE: JO986

Ingred Name:MINERAL OIL CAS:64742-52-5 RTECS #:PY0350000 Fraction by Wt: 88.0% Other REC Limit s:5MG/CUM AS OIL MIST

Ingred Name:POLYOXYETHYLENESORBITOL OLEATE CAS:9005-65-6 Fraction by Wt: 1.0%

Ingred Name:SOLUBLE BASE 5400 (FROM KIMES CORP.ALLISON PARK,PA 15101 Fraction by Wt: 11.0%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES AND SKIN & RESPIRATORY TRACT. CHRONIC:SENSITIZATION,DERMATITIS Effects of Overexposure:INHALATION OF HIGH CONCENTRATI ONS OF VAPORS MAY CAUSE HEADACHE, DIZZINESS, OR NAUSEA Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN

First Aid:INHALE: RMV TO FRESH AIR. IF NOT BRTHG GIVE CPR. IF BRTHG DIFFICULT GIVE OXYGEN. INGEST: DO NOT INDUCE VOMITING. CONTACT: IMMED FLUSH EYES OR SKIN W/ PLENTY OF WATER. RMV CONTAM CLTHG & SHOES. CALL A PHYSICIAN.

Flash Point Method:COC Flash Point:340F/171C Autoignition Temp:Autoignition Temp Text:380F Extinguishing Media:CO*2, FOAM, DRY CHEM. Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:SMALL LEAKS: ABSORB WITH NON-COMBUSTIBLE ABSORBANT, LARGE SPILLS: DIKE FOR LATER DISPOSAL. KEEP AWAY FROM SEWERS,ETC. ELIMENATE IGNATION SOURCES.

======

 Handling and Storage Precautions: KEEP CONTAINERS CLOSED, KEEP AWAY FROM HEAT AND FLAME. HANDLE AND STORE IN WELL VENTILATED AREA.
Other Precautions: WASH CONTAMINATE CLOTHING BEFORE REUSE. DISCARD OIL SOAKED SHOES.

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL. Ventilation:LOCAL EXHAUST TO ELIMINATE MIS TS/FUMES/GASES. Protective Gloves:NEOPRENE,RUBBER Eye Protection:GOGGLES OR FACESHIELD Other Protective Equipment:RUBBER BOOTS,APRON Work Hygienic Practices:AVOID CONTACT WITH EYES & SKIN;DO NOT BREATHE VAPORS/MIST. Supplemental Safety and Health MSDS RECEIVED BY DGSC-SLM:10 FEB 1988.

HCC:V6 Boiling Pt:B.P. Text:700F,371C Spec Gravity:0.93 Solubility in Water:COMPLETE Appearance and Odor:FLUID OIL,BLAND

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:OPEN FLAME Hazardous Decomposition Products:OXIDES OF CARBONS.(DECOMPOSITION PRODUCTS)

Waste Disposal Methods: ELIMINATE IGNITION SOURCES. DESTROY BY LIQUID INCINERATION. INCINERATION WILL BE EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT. HANDLE & DISPOSE IN FULL COMPL IANCE WITH ALL APPLICABLE INTERNATIONAL, F ED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respon sibility for the suitability of this information to their

particular situation.