

OCTAGON PROCESS INC -- O-P-559 -- 6810-00-264-6717

=====  
Product Identification  
=====

Product ID:O-P-559

MSDS Date:01/01/1985

FSC:6810

NIIN:00-264-6717

MSDS Number: BDQVZ

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-9400

Emergency Phone Num:201-945-9400

CAGE:82925

=== Contractor Identifica

tion ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POTASSIUM BICHROMATE (SARA III)

CAS:7778-50-9

RTECS #:HX7680000

Fraction by Wt: 100%

OSHA PEL:C,0.1 MG/M3 CRO3

ACGIH TLV:0.5 MG CR/M3; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

=====  
Hazards Identification  
=====

Effects of Overexposur

e:MAY CAUSE IRRIT OF MUCOUS MEM OR SKIN. INGEST:  
LG QTY MAY BE FATAL

=====  
First Aid Measures  
=====

First Aid:SKIN: FLUSH AREA W/WATER. REMOVE CONTAMINATED CLOTH. EYE:  
IRRIGATE EYES FOR 15 MIN. INGEST: GIVE MAGNESIA, CHALK OR WHITING  
SUSPEND IN WATER. FOLLOW W/EMETIC. GIVE OLIVE OIL OR MUCILAGINOUS  
DRINK. INH AL: IRRIGATE NASAL PASSAGE & MOUTH W/SALT-WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:N

ONE

Extinguishing Media:WATER

Fire Fighting Procedures:FLUSH W/WATER

Unusual Fire/Explosion Hazard:WILL NOT BURN OR SUPPORT COMBUSTION

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SOLID, SCOOP UP. FLUSH AREA W/WATER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN DRY AREA WHERE FLOOR CAN BE  
FLUSHED W/WATER IN EVENT OF SPILL. PERSONAL HYGIENE IMPORTANT.

Other Precautions:AVOID CO

NTACT W/SKIN OR EYES. AVOID BREATHING VAPORS

OR MISTS. DO NOT TAKE INTERNALLY. SEE MCA SAFETY SHEET SD-46 ON  
CHROMATES.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:US BUR MINES 2175 MODEL 7100 DUST RESP

Ventilation:LOCAL OR MECHANICAL AS NEEDED TO MEET TLV

Protective Gloves:RUBBER

Eye Protection:CHEM SAFETY GOGGLES

Other Protective Equipment:RUBBER APRON SLEEVES & RUBBER SAFETY SHOES.  
SAFETY SHOWER.

Supplemental Safety and Health

=====  
=====

===== Physical/Chemical Properties =====

HCC:D1

Spec Gravity:2.7

Appearance and Odor:CRYSTALLINE FREE FLOWING, ORANGE-RED, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR OXIDIZABLE MATERIALS

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:HEXAVALENT: REDUCE TO TRIVALENT-PRECIPITATE AS  
HYDROUS CHRO

MIC OXIDE. CAN USE REDUCING AGENTS SUCH AS; SODIUM  
SULFITE OR BISULFITE, SO\*2, FESO\*4. NEUTRALIZE TO PH OF 7 W/SODA  
ASH OR CAUSTIC SODA. OBSE RVE LOCAL, STATE, FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use

. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.