

ASHLAND CHEM CO. -- ETHYLENE GLYCOL MONOMETHYL ETH -- 6810-00-264-8997

=====
Product Identification
=====

Product ID:ETHYLENE GLYCOL MONOMETHYL ETH

MSDS Date:01/01/1985

FSC:6810

NIIN:00-264-8997

MSDS Number: BDQYR

=== Responsible Party ===

Company Name:ASHLAND CHEM CO.

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Info Phone Num:614-790-3333

Emergency Phone Num:606-324-1133

CAGE:81355

=== C

Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH

ZIP:43017

Country:US

Phone:614-889-4505

CAGE:5A188

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: >60%

OSHA PEL:S, 25

PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:UNIDENTIFIED COMPONENTS
Fraction by Wt: TOXIC AMOUNTS CAN BE ABSORBED THRU SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED:WEAR NIOSH/MESA APPR AIR
SUPPLIED RESPIR.

Ventilation:MECHANICAL(GEN/LOCAL EXHAUST)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:IMPERV,AS REQD TO PREVENT SKIN CONTACT

Supplemental Safety and Health

CHEMICAL NAME:EHTYL

ENE GLYCOL MONOMETHYL ETHER. NOTE:PURITY

>60%;REMAINING 40% OF PRODUCT UNIDENTIFIED.PRODUCT ALSO CALLED
METHYL CELLOSOLVE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:256F,124.4C

Vapor Pres:6.0

Vapor Density:2.6

Spec Gravity:0.966

Evaporation Rate & Reference:1(BUTYL ACETATE)

Solubility in Water:COMPLETE

Appearance and Odor:LIQUID;MILD ODOR(PER LITERATURE)

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STROG OXIDIZING AGENTS(PER LITERATURE).

Stability Condition to Avoid:IGNITION SOURCES

Hazardous Decomposition Products:TOXIC MATERIALS INCL:CO,CO*2,ETC

===== Disposal Considerations =====

Waste Disposal Methods:SM SPILL:EVAPORATE VOLATILES IN HOOD;LG
SPILL:PERMITTED INCINERATION;SOLIDS TO APPROVED LANDFILL.HANDLING
AND DISPOSAL IN FULL REGULATORY COMPLIANCE.

Disclaimer (provided wit

h this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.