

MINNESOTA MINING & MFG CO ADHESIVES & SEALERS DIV. -- 3M EC-776 FUEL RESISTANT COATING -- 8040-00-266-0818

===== Product Identification =====

Product ID:3M EC-776 FUEL RESISTANT COATING

MSDS Date:06/30/1987

FSC:8040

NIIN:00-266-0818

MSDS Number: BDRGF

=== Responsible Party ===

Company Name:MINNESOTA MINING & MFG CO ADHESIVES & SEALERS DIV.

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

C

Country:US

Info Phone Num:612-733-5454

Emergency Phone Num:612-733-5454

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====

== Composition/Information on Ingredients =====

Ingred Name:ACRYLONITRILE/BUTADIENE RUBBER

Fraction by Wt:

Other REC Limits:NK

OSHA PEL:

ACGIH TLV:

Ingred Name:PHENOL-FORMALDEHYDE RESIN

Fraction by Wt:

Other REC Limits:

OSHA PEL:

ACGIH TLV:

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 61%

Other REC Limits:N/K

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHO

L (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 7%

Other REC Limits:N/K

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 6%

Other REC Limits:N/K

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of C

arcinogenicity:NIOAH:FORMALDEHYDE AS A POTENTIAL
OCCUPATIONAL CARC.NIOSH CURRENT INTELLIGENCE BULLETIN 34.APRIL 15
1981

Effects of Overexposure:EYE:SEVERE IRRITATION.EDEMA REDNESS,TEARING,
BURN SENSATION,BLURED VISION.SKIN:IRRITATION ON PROLONG
EXPOS.INHAL:VAPOR,RESP SYSTEM IRRIT & LIGHT HEADED.MIBK VAPORS MAY
CAUSE LIVER &KIDNEY DAMAGE.SYMP
OMS:HEADACHE,DIZZY,WEAK,FATIGUE,UNCONSCIOUS.INGEST:IRRIT,LIGHT
HEADED,NAUSEA&VOMITING.ASPIRATE INTO LUNG/DAMAGE/SUP DATA

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/PLENTY OF H*2O FOR 15 MIN CALL PHYS.SKIN:WASH W/
SOAP & H*2O.INHAL:MOVE TO FRESH AIR.RESTORE/SUPPORT
BREATHING.DIFFICULTY BREATH PERSISTS,CALL PHYS.INGEST:DO NOT INDUCE
VOMITING.GIVE TWO GLASSES OF MILK OR H*2O TO DRINK.CALL PHYS.IF
SPONTANEOUS VOMITING OCCURS,LOWER HEAD BELOW HIPS TO PREVENT
ASPIRATION INTO THE LUNGS.

===== Fire Fighting Measures =====

Flash Point:50F- 10C
Lower Limits:1.4
Upper Limits:19
Extinguishing Media:CO*2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED W/SCBA WHEN
FIGHTING FIRES INVOLVING THIS MATERIAL
Unusual Fire/Explosion Hazard:FLAMMABLE.OVERHEATED,CLOSED CONTAINES
ADJACENT TO FIRE COULD EXPLODE DUE TO PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH IGNITION SOURCES.COLLECT SPILLED
MAT.CLEAN UP RE
SIDUE & STORAGE IN CLOSED METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS &
FLAME.KEEP CONTR CLOSED WHEN NOT IN USE.KEEP OUT OF THE REACH OF
CHILDREN.
Other Precautions:AVOID PROLONGED BREATHING OF VAPORS & PROLONGED OR
REPEATED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EX

POSURE OF CONCERN .

Ventilation:USE ONLY IN AREAS ADEQ VENT W/ ENOUGH AIR MOVEMENT TO REMOVE VAPORS & PREVENT VAPOR BUILD-UP.CONSULT LOCAL (SEE SUP DATA

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES

Supplemental Safety and Health

SIGNS & SYMPTOMS OF OVEREXPOSURE:OR DEATH,MEK IS A POTENTIAL EMBRYO/FETOTOXIN BASED ON LAB STUDIES.THERE IS NO EVIDENCE OF REPRODUCTIVE EFFECTS ASSOCIATED W/ HUMAN EXPOS TO MEK.VENT:SAFETY/HEALTH AUTH ORITIES IF ADDITIONAL

GUIDANCE IS NECESSARY .

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:164F-73.73C

Vapor Pres:42

Vapor Density:3.0

Spec Gravity:0.88

Evaporation Rate & Reference:>5 ETHER=1

Solubility in Water:INSOLUBLE

Appearance and Odor:TRANSPARENT AMBER THIN LIQUID CHARACTERISTIC KETONE ODOR

Percent Volatiles by Volume:74

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous De

composition Products:CO,CO*2,N & SMOKE PARTICLES,WHEN SUBJECTED TO EXCESSIVE HEAT OR FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:COMMERICAL INCINERATE W/ DESTRUCTION & REMOVAL EFFICIENCY > 99.99% OR RECLAMATION IS PREFERRED.OTHERWISE DISPOSE IAW APPLICABLE REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United S

tates of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.