

DAVIS-HOWLAND OIL CORP -- MIL-L-83767B;LUBRICATING OIL;TYPE II -- 9150-00-273-8663

===== Product Identification =====

Product ID:MIL-L-83767B;LUBRICATING OIL;TYPE II

MSDS Date:01/01/1987

FSC:9150

NIIN:00-273-8663

MSDS Number: BDSBL

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORP

Address:200 ANDERSON AVE

City:ROCHESTER

State:NY

ZIP:14607-1111

Country:US

Info Phone Num:716-473-6650

Eme

rgency Phone Num:(716) 473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTEC

S #:PY8030000
Other REC Limits:5MG/CUM,AS OIL MIST.
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES (TYPE NOT SPECIFIED)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF SKIN OR EYES.
CHRONIC:NO DATA AVAILABLE.
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE
MILD SKIN IRRITATION;MAY CAUSE EYE IRRITATION.
Medical Con
d Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT,WASH WITH SOAP & WATER;IF SPLASHED
INTO EYES FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES.GET MED
ATTN FOR EYES.

===== Fire Fighting Measures =====

Flash Point:395-475F-(COC)
Lower Limits:1.0%
Upper Limits:7.0%
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting P
rocedures:USE AIR-SUPPLD RESCUE EQUIP IN CLOSED AREA.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.USE PROTCTV
EQUIPMENTS;RECOVER FREE LIQUID.ADD ABSORBENT TO SPILL AREA.KEEP
PETROLEUM PRODUCTS OUT OF STREAMS,WATERWAYS & SEWERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS

CLOSED;KEEP AWAY FROM
HEAT & OPEN FLAMES;PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE.
Other Precautions:AVOID BREATHING OIL MIST.REMOVE OIL-SOAKED CLOTHING &
LAUNDRER BEFORE RE-USE.WASH THOROUGHLY W/SOAP & H*2O AFTER
HANDLING/EXPOSURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED
Ventilation:LOCAL EXHAUST:TO CAPTURE HOT FUMES & VAPORS.
Protective Gloves:OIL IMPERVIOUS
Eye Protection:AS REQUIRED
Other Protective Equipm
ent:USE OIL IMPERVIOUS APRON IF NEEDED.
Supplemental Safety and Health
MFR MSDS NOT DATED;ITEM IS TYPE II OF MIL SPEC MIL-L-83767B,LUBRICATING
OIL,VACUUM PUMP,MECHANICAL;SPECIFIC GRAVITY RANGE 0.87-0.90.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:545-900F
Vapor Pres:12
Spec Gravity:0.87-90
Evaporation Rate & Reference: