

ESSEX CHEMICAL CORP PRO-SEAL DIV -- STRIPPABLE VINYL COATING 67-591 -- 8030-00-275-8093

=====
Product Identification
=====

Product ID:STRIPPABLE VINYL COATING 67-591

MSDS Date:01/01/1987

FSC:8030

NIIN:00-275-8093

MSDS Number: BDSHG

=== Responsible Party ===

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Info Phone Num:310-537-

7600

Emergency Phone Num:310-537-7600

CAGE:83527

=== Contractor Identification ===

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 54.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

D

OT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:NARCOSIS, TRANSIENT EYE, & NASAL IRRITATION

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE. IN CASE OF SKIN OR EYE CONTACT, FLUSH

AFFECTED AREA WITH COPIOUS AMTS OF WATER FOR 15 MIN.

===== Fire Fighting Measures =====

Flash Point:19 F, -7 C 5CC

Lower Limits:1.8

Upper Limits:11.5

Extinguishing Media:ALCOHOL FOAM, CO*2, DRY CHEMICALS

Fire Fighting Procedures:CO*2, FOAM, DRY CHEMICAL

Unusual Fire/Explosion Hazard:HANDLE AS VERY FLAMMABLE LIQUID

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCE. STOP SPILL AT

SOURCE. CONTAIN SPILL BY DIKE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE OUT OF SUN. KEEP IN AREA AWAY FROM WARK AREA BY MEANS OF CONDUCTING FLUID THROUGH HOSES.

Other Precautions:ERECT "NO SMOKING" SIGNS.

===== Exposure Controls/Personal Protection =====

Ventilation:USE CROSS VENTILATION AND EXPLOSION PROOF MOTOR FOR LOCAL

Protective Gloves:RUBBER

Eye Protection:GLASSES W/SIDE OR GOGGLES

Supplementa

I Safety and Health
CONTAINS 0.8 % BY WEIGHT DIBASIC LEAD

===== Physical/Chemical Properties =====

HCC:F2
Spec Gravity:0.89
Evaporation Rate & Reference:1.0 BUT.ACETATE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:SILVER COLORED LIQUID,SOLVENT ODOR
Percent Volatiles by Volume:68.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

=====

Waste Disposal Methods:ABSORBE MATERIAL WITH DIATOMACEOUS EARTH OR EQUIVALENT. SHOVEL INTO METAL CONTAINER. DISPOSE BY LIQUID INCINERATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.