

UNION CHEMICALS DIV,UNION OIL COMP OF CALIFORNIA -- AMSCO SOLV 1005,REGULAR
MINERAL SPIRITS -- 6850-00-281-1985

===== Product Identification =====

Product ID:AMSCO SOLV 1005,REGULAR MINERAL SPIRITS

MSDS Date:01/01/1987

FSC:6850

NIIN:00-281-1985

MSDS Number: BDSPR

=== Responsible Party ===

Company Name:UNION CHEMICALS DIV,UNION OIL COMP OF CALIFORNIA

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

Sta

te:IL

ZIP:60195

Country:US

Info Phone Num:312-619-2644

Emergency Phone Num:312-619-2644

CAGE:DO714

=== Contractor Identification ===

Company Name:UNION CHEMICALS DIVISION

Address:1345 NORTH MEACHAM ROAD

Box:7600

City:SCHAUMBURG

State:IL

ZIP:60196

Phone:213-664-2121 OR 800-424-9300

CAGE:DO714

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

===== Composition/Information

on Ingredients =====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: >95%.
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:EYES:MAY IRRITATE SKIN:MAY IRRITATE &
DERMATITIS.INHAL:IRRITATES RESPIR.TRACT,CNS DEPRESSION IN H.C.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:F
LUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:105F/40.5C (CC)
Lower Limits:UNKN
Upper Limits:UNKN
Extinguishing Media:USE FOAM CO*2,DRY CHEMICAL
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA FOR
FIREFIGHTERS.USE WATERSPRAY
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL
SURFACES AND
OTHER SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SOURCES OF IGNITION AWAY.FLUSH SPILLED
MATERIAL INTO SUITABL RETAINING AREAS.SMALL AMOUNTS OF SPILLED
MATERIAL MAY BE ABSORBED INTO AN APPROPRIATE ABSORBANT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT CONTAINERS COOL AND AWAY
FROM SOURCES OF IGNITION.PROVIDE ADEQUATE VENTILATION.

Other

Precautions:DO NOT INHALE VAPORS.AVOID SKIN & EYES CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSAH APPROVED RESPIRATOR FOR ORGANIC SOLVENT OR THIS ITEM

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1

Spec Gravity: