

MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION -- CUPRIC SULFATE -- 6810-00-281-2035

===== Product Identification =====

Product ID:CUPRIC SULFATE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-281-2035

MSDS Number: BDSQY

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION

Emergency Phone Num:(314)982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPE

CIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

===== Composition/Information on Ingredients =====

Ingred Name:CUPRIC SULFATE PENTAHYDRATE; CAS #7758-99-8.

CAS:7758-99-8

RTECS #:GL8900000

Fraction by Wt: >99%

ACGIH TLV:1MG/CUM(CU DUST

===== Hazards Identification =====

Effects of Overexposure:INH:IRRIT UPPER RESP TRACT;ING:MAY BURN

MOUTH,ESOPHAGUS,VOMITG,H

EADACHE;SKIN/EYES:IRRIT,RDNSS,PAIN.

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR.GIVE CPR/OXYGEN IF BREATHING IS

DIFFICULT.GET MD;INGEST:IMMED INDUCE VOMIT BY GIVING 2 GL OF

WATER.NOTHING BY MOUTH IF UNCONSCIOUS.GET MD IMMED;SKIN/EYES:FLUSH

IMMED W/LG QTY H* 20 FOR 15 MIN.RMV CONTMNTD CLOTHES.GET MED ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:EXTINGUISH W.

AGENT SUITABLE FOR SURROUNDING FIRE.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:NOT CONSIDERED TO BE AN EXPLOSION HAZARD;SCALED CONTNRS MAY RUPTURE DURING FIRE DUE TO PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA OF SPILL.CLEAN UP PERSONS NEED PROTCTV CLOTHG/RESP PROTCTION FM DUST.PICK UP SPILL & PLACE IN A SUITABLE CONTAINER FOR RECLAMATION OR DISPOSAL IN A METHOD THAT DOES NOT GENERATE DUST;DO NOT FLUSH TO SEWER.TOXIC TO FISH

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHTLY CLOSED CONTNRS AT COOL,DRY,VENTILATED PLACE.PROTECT AGAINST PHY DAMAGE.ISOLATE FROM INCOMPATIBLE SUBSTANCES.SOLN IS CORR TO MILD STEEL
Other Precautions:AVOID BREATHING DUST.USE W/ADEQUATE VENTILATION.KEEP CONTAINRS CLOSED.WASH THOROUGHLY AFTER HANDLING.AVOID SKIN,EYES & CL
OTHING CONTACT;SOLUTIONS ARE ACIDIC,REACT W/MAGNESIUM TO GIVE HYDROGEN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DUST/MIST RESPIR
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION
Supplemental Safety and Health
MSDS FM MFR DATED 05AUG85,CONFORMS TO OSHA HAZ COMM STD; MELTING PT:LOSES WATE @1
10C(230F); DECOMPOSES ABOVE 400C(752F).

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:2.28
Solubility in Water:APPRECIABLE
Appearance and Odor:TRNSPRNT BLUE CRYSTLN CRANULES/POWDER.ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
>250C THE ANHYDROUS SALT WILL IGNITE HYDROXYLAMIN.
Hazardous Decomposition Products:EMITS OXIDES OF SULFUR & COPPER WHEN HEATED TO DECOMPOSITION

==

===== Disposal Considerations =====

Waste Disposal Methods:WHATEVER CANNOT BE SAVED FOR RECLAMATION MAY BE
DISPOSAL AS HAZ WASTE IN A RCRA APPRVD WASTE DISPOSAL
FACILITY.COMPLY WITH LOCAL,ST. & FED REGS; CWA/CERCLA
RQ:10LBS(ANHYDROUS).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly
or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.