

UNION CHEMICALS DIVISION,UNION OIL COMP OF CALIFOR -- AMSCO SOLV 1005,REGULAR
MINERAL SPIRITS -- 6850-00-281-3061

===== Product Identification =====

Product ID:AMSCO SOLV 1005,REGULAR MINERAL SPIRITS

MSDS Date:01/01/1987

FSC:6850

NIIN:00-281-3061

MSDS Number: BDSXT

=== Responsible Party ===

Company Name:UNION CHEMICALS DIVISION,UNION OIL COMP OF CALIFOR

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Info Phone Num:312-619-2644

Emergency Phone Num:312-619-2644

CAGE:DO714

=== Contractor Identification ===

Company Name:UNION CHEMICALS DIVISION

Address:1345 NORTH MEACHAM ROAD

Box:7600

City:SCHAUMBURG

State:IL

ZIP:60196

Phone:213-664-2121 OR 800-424-9300

CAGE:DO714

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

===== Composition/Informat

ion on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 100%.

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:EYES:EYE IRRITANT.SKIN:SKIN
IRRITANT,DERMATITIS.RESPIRATORY TRACT IRRITATION.CNS DEPRESSION IN
H.CON

===== Fire Fighting Measures =====

Flash Point:100-200F

Lower Limits:UNKN

Upper Limits:UNKN

Extinguis

hing Media:USE FOAM,CO*2,OR DRY CHEMICALS

Fire Fighting Procedures:USE NIOSH APPROVED SCBA FOR FIRE
FIGHTING.WATER SPRAY-COOL C

Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL
SURFACES & OTHER SOURCES OF IGNITION

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SOURCES OF IGNITION AWAY FROM THE
SPILL.FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREAS SMALL
SPILLED MATERIALS MAY BE ABSORBED INTO AN APPROPRIATE AB
SORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS COOL,DRY & AWAY FROM
SOURCES OF IGNITION.USE & STORE THIS PRODUCT WITH ADEQUATE
VENTILATION.

Other Precautions:DO NOT INHALE VAPORS.AVOID SKIN & EYES CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPOR TYPE.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT

TO MAINTN 1.0

Spec Gravity: