

NAZ-DAR COMPANY -- TT-F-325,LACQUER,CELLULOSE, ALL PUR WHT -- 8010-00-281-4787

=====
Product Identification
=====

Product ID:TT-F-325,LACQUER,CELLULOSE, ALL PUR WHT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-281-4787

MSDS Number: BDSZQ

=== Responsible Party ===

Company Name:NAZ-DAR COMPANY

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

CAGE:EO327

=== Contractor Identifi

cation ===

Company Name:NAZ-DAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622

Country:US

Phone:312-943-8338

CAGE:EO327

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4292

Country:US

Phone:312-943-8338;800-736-7636

CAGE:76708

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40.0%

OSHA PEL:100 PPM

=====

=====
===== Hazards Identification =====

Effects of Overexposure:INH: ANESTHETIC. IRRIT OF RESP TRACT OR ACUTE
CNS DEPRESS, HDCH, DIZZ, UNCON, COMA. EYE/SKIN: IRRIT

=====
===== First Aid Measures =====

First Aid:INH: REMOVE FROM EXP. RESTORE BREATH. KEEP WARM/QUIET. CNTCT
MD. EYES: IMMED FLUSH W/LG AMT WATER AT LEAST 15 MIN. TAKE TO MD
FOR MED TREATMENT. SKIN: REMOVE W/SOAP & WATER. REMOVE CONTAM
CLOTHING.

=====
===== Fire Fighting Measures =====

Flash Point:106F SCC

Lower Limits:1

Extinguishing Media:USE NFPA CL B EXTINGUISHERS, CO*2, DRY CHEM, FOAM

Fire Fighting Procedures:WATER SPRAY INEFF. WATER-COOL EXP CNTNR. USE
FOG NOZZ.

Unusual Fire/Explosion Hazard:CLOSED CNTNRS MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT. DO NOT APPLY TO HOT SURFACES. AVOID IGNITE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. A
VOID BRTHNG VAPOR.

VENT AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTY
IN BLDGS DESIGNED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQ.

Other Precautions:DO NOT TAKE INTERNALLY. GROUND CNTNRS WHEN POURING.
AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT, WELD
OR BRAZE W/O APP RESP. WELDING PRODUCES HAZ DECOMP FUMES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPRVD RESP

Ventilation:GEN DILUT OR LOCAL EXH TO KEEP