

TECH SPRAY,INC -- TT-B-846,BUTYL ALCOHOL:NORMAL(BUTANOL) -- 6810-00-281-6928

===== Product Identification =====

Product ID:TT-B-846,BUTYL ALCOHOL:NORMAL(BUTANOL)

MSDS Date:01/01/1985

FSC:6810

NIIN:00-281-6928

MSDS Number: BDTBM

=== Responsible Party ===

Company Name:TECH SPRAY,INC

Address:88 HUGHES STREET

Box:949

City:AMARILLO

State:TX

ZIP:79105

Country:US

Info Phone Num:800-692-4677 OR 800-858-40

43

Emergency Phone Num:806-372-8523

CAGE:JO768

=== Contractor Identification ===

Company Name:TECH SPRAY INC

Address:1001 NW 1ST

Box:949

City:AMARILLO

State:TX

ZIP:79105-0949

Country:US

Phone:806-372-8523

CAGE:54700

Company Name:TECH SPRAY,INC

Address:88 HUGHES STREET

Box:949

City:AMARILLO

State:TX

ZIP:79105

Country:US

Phone:800-692-4677 OR 800-858-4043

CAGE:JO768

===== Composition/Information on Ingredients =====

Ingred Name:BUTYL ALCOHOL(N-BUTANOL)(CAS #71-36-3)

RTECS #:OE1

400000
Fraction by Wt: 100%
ACGIH TLV:(C) 50 PPM

===== Hazards Identification =====

Effects of Overexposure:IRRITANT TO EYES &
SKIN,ANESTHETIC,CONJUNCTIVITIS,DERMATITIS,RESPIRATORY
INFLAMMATION,HEADACHE

===== First Aid Measures =====

First Aid:FLUSH EYES THOROUGHLY WITH WATER.WASH OUT CONTAMINATED SKIN
WITH SOAP & WATER.APPLY OPHTHALMIC CORTISONE FOR CONJUNCTIVITIS &
KERATITIS.STOMACH WASH,IF SWALLOWED,FOLLOWED BY SALINE CATHARIS.

===== Fire Fighting Measures =====

Flash Point:105F TOC
Extinguishing Media:WATER,DRY CHEMICAL,CARBON DIOXIDE,FOAM MAY BE
INEFFECTIVE
Fire Fighting Procedures:WATER SPRAY MAY HELP TO KEEP CONTAINERS
COOL,TO DIFFUSE GAS.
Unusual Fire/Explosion Hazard:SOURCES OF IGNITION,REACTS WITH
EXPLOSIVES,OXIDIZING MATERIALS,ORGANIC PEROXIDES,POISONS,& ISOTOPES

===== Accidental Release Measures =====

Spill
Release Procedures:REMOVE LEAKING PACKAGES TO SAFE AREA,AWAY FROM
FIRE OR FLAME,AVOID BREATHING CONCENTRATED VAPORS

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,UNLIGHTED PLACE AWAY
FROM SOURCES OF IGNITION & FROM EXPLOSIVES,OXIDIZING
MATERIALS,ORGANIC PEROXIDES,POISONS & RADIOACTIVE MAERIALS.
Other Precautions:DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F.DO
NOT DROP CONTAINERS.WEAR SAFETY GLASSES,SELF CO

NTAINED BREATHING

APPARATUS & RUBBER PROTECTIVE CLOTHING.AVOID PROLONGED OR BREATHING
OF GASES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS

Ventilation:AS REQUIRED TO CONTROL THE TLV IN AIR

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:RUBBER PROTECTIVE CLOTHING

Supplemental Safety and Health

FED SPEC TT-B-846 HAS BEEN CANCELLED EFFECTIVE AUT 21,1979;STORAGE CODE
F3

IS ASSIGNED ON THE BASIS OF THAT FLASH PT IS LOWER THAN 100F.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:244F

Spec Gravity:0.8109

Evaporation Rate & Reference:N.A.

Appearance and Odor:CLORLESS LIQUID,FUSEL OIL OR WINE LIKE ODOR

Percent Volatiles by Volume:7.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING/CORROSIVE MATL.

Stability Condition to Avoid:SOURCE OF IG

N.

Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CANS.SPRAY MAERIAL INTO A

FURNACE UNDER CONTROLLED PROCEDURES.INCINERATION WILL BECOME EASIER
BY MIXING WITH A MORE FLAMMABLE SOLVENT

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner what

soever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.