

US WAX INC. -- PETROLEUM WAX:USW#135-140 -- 9160-00-285-2045

===== Product Identification =====

Product ID:PETROLEUM WAX:USW#135-140

MSDS Date:01/01/1987

FSC:9160

NIIN:00-285-2045

MSDS Number: BDTLZ

=== Responsible Party ===

Company Name:US WAX INC.

Emergency Phone Num:215-757-3740

CAGE:LO157

=== Contractor Identification ===

Company Name:U S WAX INC

Address:618 N WOODBOURNE RD

Box:City:LANGHORNE

State:PA

ZIP:19047

Country:US

CAGE:4W679

Company Name:US WAX INC.

CAGE:LO157

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM WAX BLEND (PER MFR,TAKE TLV AS OIL MIST =5MG/CUM)

Fraction by Wt: 100%

===== Hazards Identification =====

Effects of Overexposure:EYES:MILD IRRIT;SKIN:WILL SOFTEN CALLOUSED

SKIN;INHAL:RESP.TRACT IRRIT.INGEST:MAY ACT AS LAXATIVE.

===== First Aid Measures =====

=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;

GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER

SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>400F/204C

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATERFOG

Fire Fighting Procedures:TREAT AS OIL FIRE;USE NIOSH/MSHA APPROVED SCBA

IN CONFINED A

Unusual Fire/Explosion Hazard:PR

ODUCTS OF COMBUSTION-SMOKE,CO & CO*2

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;SCRAPE UP MATERIAL INTO WASTE CONTAINERS.CLEAN THE AREA WITH DETERGENT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM HEAT,OPEN FLAME & OXIDIZING MATERIALS.

Other Precautions:AVOID PERSONAL CONTACT;WASH WITH SOAP AND WATER AFTER EA
CH USE.DO NOT SMOKE,EAT OR DRINK IN WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG.VAPORS/MIST IF ABOVE TLV.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED:NIL;PLANT LO

CATION PHONE #609-695-6771

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:NIL

Spec Gravity:0.8035

Evaporation Rate & Reference:0.0 (ETHYL ETHER=1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE WAX (SOLID AT ROOM TEMP.)ODORLESS

Percent Volatiles by Volume:0.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXTREME HEAT,OPEN F

LAME

Hazardous Decomposition Products:NONE NOTED BY MFR.PROD OF
COMBUSTION:CO AND CO*2 OR SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expre

ssly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.