

CON-LUX COATINGS,INC. -- ENAMEL,ALKYD,GLOSS 16187 -- 8010-00-286-7749

=====  
Product Identification  
=====

Product ID:ENAMEL,ALKYD,GLOSS 16187

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7749

MSDS Number: BDTXN

=== Responsible Party ===

Company Name:CON-LUX COATINGS,INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergency Phone Num:201

-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 43.9%

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITATION OF E

YES AND SKIN. IRRITATION OF  
RESPIRATORY TRACT. HEADACHE OR DIZZINESS.

=====  
First Aid Measures  
=====

First Aid:SKIN/EYES:FLUSH WITH WATER.INHAL:MOVE TO FRESH AIR.IF  
IRRITATION PERSISTS,CALL DR.

=====  
Fire Fighting Measures  
=====

Flash Point:40.6/105

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CLASS B EXTINGUISHERS (CO\*2,DRY CHEM.OR FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PRE  
VENT

AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND  
ISOLATE FROM SOURCES OF IGNITION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT  
SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING OF  
VAPORS.VENTILATE AREA. REMOVE WITH NON-SPARKING TOOLS AND INERT  
ABSORBENT.

=====  
Handling and Storage  
=====

Handling and

Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP  
AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED  
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM/MECH FILTER  
RESPIRATOR

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GLGGLES OR GLASSES

Other Protective Equipment:PREVEN

T PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY  
TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:157.2/315

Vapor Pres:1

Vapor Density:4.7

Spec Gravity:1.04

Evaporation Rate & Reference:BUAC=1:0.15

Solubility in Water:0

Appearance and Odor:GRAY LIQUID,MILD ALIPHATIC ODOR

Percent Volatiles by Volume:59.5

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DOSPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND  
FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense.

The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.