

GRAHAM PAINT & VARNISH CO, INC -- TT-P-102E -- 8010-00-290-4049

=====  
Product Identification  
=====

Product ID:TT-P-102E

MSDS Date:01/01/1985

FSC:8010

NIIN:00-290-4049

MSDS Number: BDVDM

=== Responsible Party ===

Company Name:GRAHAM PAINT & VARNISH CO, INC

Emergency Phone Num:312-376-7676

CAGE:EO554

=== Contractor Identification ===

Company Name:GRAHAM PAINT & VARNISH CO., INC.

CAGE:EO554

Company N

ame:GRAHAM PAINT AND VARNISH CO INC

Address:4800 S RICHMOND AVE

Box:City:CHICAGO

State:IL

ZIP:60632-2022

Country:US

Phone:312-376-7676

CAGE:61945

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 16.2%

ACGIH TLV:500 PPM

Ingred Name:PIGMENTS

Fraction by Wt: 49.6%

Ingred Name:VEHICLE

Fraction by Wt: 33.6%

Ingred Name:ADDITIVE

Fraction by Wt: 0.6%

=====  
Hazards Identification  
=====

=====

Effects of Overexposure:EYES-SEVERE IRRITATION. SKIN-IRRITATION OR DERMITITIS; INHALE-RESPIRATORY IRRITATION.

===== First Aid Measures =====

First Aid:EYES-FLUSH W WATER; GET MEDICAL HELP. SKIN-WASH W SOAP & WATER; USE EMOLLIENT CREAM; INHALE-MOVE TO FRESH AIR. SWALLOWED-DO NOT INDUCE VOMITING; GET MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point:102F, 39C TCC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:REGULAR FOAM, CO2 OR DRY CHEMICAL

Fire Fighting Procedures:WATER STREM WILL SPREAD OIL FIRES

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR & MAY MOVE ALONG GROUND & BE IGNITED BY HEAT, PILOT LIGHTS OR IGNITION SOURC

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. ABSORB ON INERT MATERIALS. DISPOSE OF IN CLOSED CONTAINERS.

===== Handling and Storage

=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT & OPEN FLAME

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ABOVE REC TLV USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:TO KEEP EXPOSURE BELOW TLV LEVEL

Protective Gloves:IMPERVIOUS ONES

Eye Protection:RECOMMEND SAFETY GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT WETTING CLOTHES.

Supplemental Safety and Health

===== Physical/Chemical P

roperties =====

HCC:F4

Boiling Pt:B.P. Text:315-380F

Vapor Pres:2.0

Vapor Density:4.9

Spec Gravity:1.42

Evaporation Rate & Reference:70/ETHER

Solubility in Water:INSOL

Appearance and Odor:COLORED OPAQUE LIQUID WITH SLIGHT ALIPHATIC ODOR

Percent Volatiles by Volume:30.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CO<sub>2</sub>, CO, VARIOUS HYDR

OCARBONS

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR LANDFILL IN ACCORDANCE WITH  
FEDERAL, STATE, AND LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.