View NSN Online: https://aerobasegroup.kr/nsn/8010-00-290-4050

CORONADO PAINT CO INC.308 OLD COUNTRY EDGEWATER FL -- WHITE -- 8010-00-290-4050

Product ID:WHITE MSDS Date:01/01/1987 FSC:8010 NIIN:00-290-4050 **MSDS Number: BDVDN** === Responsible Party === Company Name: CORONADO PAINT CO INC. 308 OLD COUNTRY EDGEWATER FL Emergency Phone Num:904-428-6461 CAGE:33200 === Contractor Identification === Company Name: CORONADO PAINT COMPAN Y. INC. Address:308 OLD COUNTY ROAD Box:City:EDGEWATER State:FL ZIP:32132-1812 Country:US Phone:904-428-6461 CAGE:33200

Ingred Name:ALKYD RESIN Fraction by Wt: 30.0%

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT) CAS:8002-05-9 RTECS #:SE7449000 Fraction by Wt: 19.0% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 8990

Effects of Overexposure: PRODUCES S

## EVERE IRRITATION DRYING OF SKIN EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA.

======================================
First Aid:EYE CONTACT FLUSH W/WATER,SKIN CONTACT WASH W/MILD SOAP & WATER & APPLY SKIN CREAM. INHALATION REMOVE TO FRESH AIR.AND CALL MD. APPLY ARTIFICIAL RESPIRATION,IF NECESSARY.
======================================
Flash Point:102F SETA Lower Limits:0.8 Upper Limits:5.0 Extinguishing Media:FO AM CARBON DIOXIDE DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE Unusual Fire/Explosion Hazard:VAPOR MAY EXPLODE WHEN MIX WITH AIR
======================================
Spill Release Procedures:WEAR A RESPIRATOR FLUSH W/WATER INTO-RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS,FIRE OR HOT METAL SURFACE.
======================================
Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN
FLAME.USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN CONTACT.
======================================
Respiratory Protection:SELF CONTAINED NIOSH APPROVED RESPIRATOR IF NECESSARY. Ventilation:KEEP AWAY FROM HEAT Protective Gloves:NIOSH APPROVED Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:EYE BATH & SAFETY SHOWER. Supplemental Safety and Health
======================================

oiling Pt:B.P. Text:315 F 157 C Vapor Pres:80 Vapor Density:4.9 Spec Gravity:0.913 Evaporation Rate & amp; Reference:SLOWER THAN NBUACT Solubility in Water:INSOLUBLE Appearance and Odor:PETROLEUM DISTILLATE ODOR WHITE ORANGE LIQUID Percent Volatiles by Volume:64.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:EXCESSIVE HEAT,SPARK,OPEN FLAMES. Hazardous Decomposition Products:THERMAL D ECOMPOSITION MAY YIELD CARBON MONOXIDE.

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabilit

y for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.