

DOW CORNING CORPORATION -- D.C.(R) 111 VALVE LUBRICANT AND SEALANT --
6850-00-294-0860

===== Product Identification =====

Product ID:D.C.(R) 111 VALVE LUBRICANT AND SEALANT

MSDS Date:03/12/1986

FSC:6850

NIIN:00-294-0860

MSDS Number: BDVTJ

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-

496-5900

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

Stat

e:KY
ZIP:42701-9804
Country:US
Phone:502-737-6757
CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:NO HAZARD INGREDIENTS STATED BY MANUFACTURERS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES:MAY CAUSE TEMPORARY
DISCOMFORT;SKIN:SINGLE,PROLONGED EXPOSURE CAUSES NO KNOWN ADVERS
E
EFFECT;INH:NO IRRIT TO NOSE/THROAT EXPECTED.NO INJURY LIKELY FROM
SHORT EXPOSURE;ING:AMTS TRANSFERRED TO MOUTH BY FINGERS IN NORMAL
OPNS SHOULD NOT CAUSE INJURY; CHRONIC:NO KNOWN ADVERSE CHRONIC
HEALTH EFFECTS.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS ON
CERTAIN INDIVIDUALS.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH WITH WATER;SKIN:WIPE OFF AND FLUSH WIT
H
WATER;INHALATION:NO PROBLEM;INGESTION:NO PROBLEM.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:>250F,>121C
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM AND
OTHER.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORN

ING

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES. PLACE IN SUITABLE DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT, SHOCK, FRICTION. KEEP CONTAINERS CLOSED.

Other Precautions: TRACES OF FORMALDEHYDE & OTHER THERMA

L

DECOMP. PRODUCTS MAY FORM AT TEMPS ABOVE 302F (150C) IN THE PRESENCE OF AIR. PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE SHOULD BE NEEDED ON NORMAL USE.

Ventilation: MECHANICAL (GENERAL) VENTILATION RECOMMENDED.

Protective Gloves: AS REQUIRED

Eye Protection: SAFETY GLASSES

Work Hygienic Practices: GOOD PRACTICE REQUIRES THAT GROSS AMTS OF ANY CHEM. BE REMOVED FROM THE SKIN ASAP, ESPECIALLY BEFORE EATING, SMOKING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: >300F, >149C

Vapor Pres: