

PRATT AND LAMBERT INC -- 741-610 -- 8010-00-297-0556

===== Product Identification =====

Product ID:741-610  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-297-0556  
MSDS Number: BDVYN  
=== Responsible Party ===  
Company Name:PRATT AND LAMBERT INC  
Address:945 BURLINGTON  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
Emergency Phone Num:316-733-1361  
CAGE:92216  
=== Contractor Identification ===  
Company Name:PRATT  
AND LAMBERT INC  
Address:945 BURLINGTON  
Box:206  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 35.0%  
OSHA PEL:100 PPM

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 0.24%  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:AROMATIC 1

00  
Fraction by Wt: < 5%  
ACGIH TLV:200 PPM

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO  
AIRWAY;IRRITATION-SKIN/EYE. HEADACHE,DIZZY,COMA.

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH WITH PLENTY OF WATER.REMOVE CONTAMINATED  
CLOTHING.INHAL:REMOVE TO FRESH AIR. CALL MD. IF NEEDED.

===== Fire Fighting Measures =====

Flash Po  
int:104 F, 40 C, TCC  
Lower Limits:1.1  
Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE  
FIRE  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARTUS AVAILABLE  
FOR FIREMEN.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION  
(FLAMES,SPARKS...)AVOID BREATHING VAPORS.VENTILATE AREA. REMOVE  
  
WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS  
ONE FLAMMABLE(OR COMBUSTABLE)LIQUID.  
Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED  
WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME  
CUT,BRAZE, OR WELD COATED MATERIAL W/O VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING

Supplemental Safety and Health

BOILING RANGE:155-189 C.

===== Physical/Chemical Properties ==

=====

HCC:F4

Boiling Pt:B.P. Text:311-373 F

Evaporation Rate & Reference: