

PRATT & LAMBERT - WICHITA DIV. -- 741-410:TT-E-527C COMP L,34087 OLIVE DRB --
8010-00-297-0560

=====
===== Product Identification =====

Product ID:741-410:TT-E-527C COMP L,34087 OLIVE DRB

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0560

MSDS Number: BDVYQ

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIV.

Emergency Phone Num:(316) 733-1361

CAGE:PRATT

=== Contractor Identification ===

C

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

OSHA PEL

:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:MAGNESIUM SILICATE

Ingred Name:DIATOMACEOUS SILICA

===== Hazards Identification =====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE: IRRIT

===== First Aid Measures =====

First Aid:IN CAS
E OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.
CALL A PHYSICIAN IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:104F TCC
Lower Limits:1.1
Extinguishing Media:SM FIRES: CO*2, DRY CHEM. LG FIRES: POLYMER FOAM
PREFERRED
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLO
DE DUE TO PRESSURE BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT
SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT &
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTY
IN BUILDINGS DESIGNED TO COMPLY W/

OSHA 1910.106. DO NOT TAKE

INTERNALLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DOT: COMBUSTIBLE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESTRICT VENT: CHEM-MECH FLTR.

CLSD: AIR-LINE TYPE

Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL

BELOW LIMIT, REMV

FUME

Protective Gloves:YES

Eye Protection:YES, FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

ADDRESS:630 EAST 13TH,ANDOVER,KS 67002.THIS PRODUCT IS AN ENAMEL ALKYD

LUSTERLESS.VAPOR PRESS BASED ON MINERAL SPIRITS IS 3.2.VAPOR

DENSITY:HEAVIER THAN AIR.WT PER GAL:10.4.

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference

:SLOWER THAN ETHER

Percent Volatiles by Volume:59.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED., STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This infor

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.