

AMERON PROTECTIVE COATIONS -- GREY 36231 -- 8010-00-297-0802

=====
Product Identification
=====

Product ID:GREY 36231
MSDS Date:01/01/1985
FSC:8010
NIIN:00-297-0802
MSDS Number: BDWCP
=== Responsible Party ===
Company Name:AMERON PROTECTIVE COATIONS
Address:201 N BERRY STREET
City:BREA
State:CA
ZIP:92621
Country:US
Info Phone Num:714-529-1951
Emergency Phone Num:714-529-1951
CAGE:0Y2E4
=== Contrac
tor Identification ===
Company Name:AMERON PROTECTIVE COATINGS
Address:201 NORTH BERRY STREET
Box:1020
City:BREA
State:CA
ZIP:92622-1020
Country:US
Phone:714-529-1951
CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL BENZENE *98-2*
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: LT5%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ACETATE
CAS:110-19-0
RTECS #:AI4025

000
Fraction by Wt: LT5%
Other REC Limits:150 PPM
OSHA PEL:150 PPM
ACGIH TLV:713 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 22.0%
Other REC Limits:STEL 400 PPM
OSHA PEL:100 PPM
ACGIH TLV:300 PPM

Ingred Name:ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 10.0%
Other REC Limits:50 PPM
OSHA PEL:300 MG/CUM
ACGIH TLV:152 MG/CUM
EPA Rp
t Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE
Effects of Overexposure:ANESTHETIC,IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER
AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A
PHYSICIAN IF CONDITIONS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:50F
Lower Limits:0.9
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

=====
===== Acci

idental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INET ABSORBENT NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:223-290F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percen

t Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formula

ted for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.