View NSN Online: https://aerobasegroup.kr/nsn/8010-00-297-2119

Product ID:BLUE 35109 MSDS Date:01/01/1987 FSC:8010 NIIN:00-297-2119 **MSDS Number: BDWGH** === Responsible Party === Company Name: AMERON PROTECTIVE COATINGS Address:201 NORTH BERRY STREET City:BREA State:CA ZIP:92622-1020 Country:US Info Phone Num:714-529-1951 Emergency Phone Num:714-529-1951 CAGE:0Y2E4 == = Contractor Identification === Company Name: AMERON PROTECTIVE COATINGS Address:201 NORTH BERRY STREET Box:1020 City:BREA State:CA ZIP:92622-1020 Country:US Phone:714-529-1951 CAGE:0Y2E4 Ingred Name: ETHYL BENZENE *98-2* CAS:100-41-4 RTECS #:DA0700000 Fraction by Wt: 1.54% Other REC Limits:100 PPM OSHA PEL:435 MG/CUM ACGIH TLV:434 MG/CUM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: BENZIN, NAPHTHA, MINERAL SPIRITS,

PETROLEUM NAPHTHA CAS:8030-30-6 RTECS #:DE3030000 Fraction by Wt: 34.5% Other REC Limits:STEL 400 PPM OSHA PEL:100 PPM ACGIH TLV:300 PPM Ingred Name: ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL CAS:78-83-1 RTECS #:NP9625000 Fraction by Wt: 6.77% Other REC Limits:50 PPM OSHA PEL:300 MG/CUM ACGIH TLV:152 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: CELLOSOLVE ACETATE (ETHYLENE GLYCOL ETHYL ETHER ACETATE), 2-ETHOXYETHYL ACETATE CAS:111-15-9 RTECS #:KK8225000 Fraction by W t: 0.56% OSHA PEL:100 PPM ACGIH TLV:5 PPM SKIN Ingred Name: ACETIC ACID, ETHYL ESTER, ETHYL ACETATE *98-2* CAS:141-78-6 RTECS #:AH5425000

Fraction by Wt: 3.0% Other REC Limits:400 PPM OSHA PEL:1400 MG/CUM ACGIH TLV:1400 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRAT

ORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

First Aid: IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST Flash Point Method:TCC Flash Point:24F Lower Limits:0.9 Extinguishing Media: SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE **FIRES-FOAM** Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY **EXPLODE** Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES. Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY Supplemental Safety and Health RESPIRATOR USE BA

SED ON CHEM. CONC. AND CONDITIONS OF USE

Boiling Pt:B.P. Text:158-290F Vapor Density:>1 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:66.2

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

Waste Dispos

al Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professio nal advice to verify and assume responsibility for the suitability of this information to their particular situation.