

PRESERVATIVE PAINT COMPANY -- S-1501 TT-V-51F -- 8010-00-299-0214

===== Product Identification =====

Product ID:S-1501 TT-V-51F

MSDS Date:01/01/1987

FSC:8010

NIIN:00-299-0214

MSDS Number: BDWLM

=== Responsible Party ===

Company Name:PRESERVATIVE PAINT COMPANY

Address:5410 AIRPORT WAY S

Box:80387

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

=== Contractor Identification ===

Company Name:

Company Name:PRESERVATIVE PAINT CO

Address:5410 AIRPORT WAY S

Box:80387

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

===== Composition/Information on Ingredients =====

Ingredient Name:PARAFFIN WAX

CAS:8002-74-2

RTECS #:RV0350000

Fraction by Wt: 93.0%

OSHA PEL:2 MG/M3 (FUME)

ACGIH TLV:2 MG/M3 (FUME); 9192

Ingredient Name:AROMATICS(HEAVIER THAN XYLENE)

Fraction by Wt: 7.0%

===== Hazards Identification =====

Effects of Overexposure:INHALTN OF HI

CONC.OF VAP.MAY LEAD TO  
ASPHYXTN.REMOVE PROMPTLY TO FRESH AIR.

=====  
First Aid Measures  
=====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG  
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE  
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

=====  
Fire Fighting Measures  
=====

Flash Point:104F/40C,TCC  
Lower  
Limits:0.8  
Upper Limits:6.8  
Extinguishing Media:CO\*2 DRY CHEMICAL

=====  
Accidental Release Measures  
=====

Spill Release Procedures:EXTINGUISH ALL SOURCES IF IGNITION IN VICINITY  
OF SPILL OR RELEASE VAPORS. CLEAN UP SPILLS AS SOON AS POSSIBLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,WELL VENTILATED AREA  
AWAY FROM SOURCES OF IGNITION.

=====  
Exposure Controls/Personal Protect  
ion  
=====

Respiratory Protection:ORG.VAP.RESPIRATOR OR GAS MASK/USE SCBA IF  
CONC.EXCEEDS TLV.  
Ventilation:LOCAL EXHAUST IF CONC.OF VAP.IS EXCESSIVE.  
Protective Gloves:NEOPRN.OR RUBBR  
Eye Protection:CHEM.SFTY GOGGLES  
Supplemental Safety and Health  
B.P. RANGE:155-197C--UNDATED MSDS

=====  
Physical/Chemical Properties  
=====

HCC:F4  
Boiling Pt:B.P. Text:311-386F  
Vapor Pres:16.  
Vapor Density:4.8  
Spec Gravity:0.7914  
Appearance and Odor:BLACK  
Percent Volatiles

by Volume:100.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
MAY REACT WITH STRONG OXIDIZING MATERIALS.  
Hazardous Decomposition Products: NORMAL COMBUST: CO\*2 &  
WATER--INCOMPL.COMBUST: CO.

===== Disposal Considerations =====

Waste Disposal Methods: ABSORB LARGE SPILLS WITH CLAY, DIATOMACEOUS  
EARTH. DISPOSE OF IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information  
by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.