

TEXACO, INC. -- 00703 REGAL OIL R&O 68 -- 9150-00-397-2852

===== Product Identification =====

Product ID:00703 REGAL OIL R&O 68

MSDS Date:01/01/1985

FSC:9150

NIIN:00-397-2852

MSDS Number: BDXNB

=== Responsible Party ===

Company Name:TEXACO, INC.

Emergency Phone Num:914-831-3400, X406

CAGE:EO421

=== Contractor Identification ===

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

C

Country:US

Phone:914-831-3400

CAGE:7B131

Company Name:TEXACO, INC.

Box:509

CAGE:EO421

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: > 95%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:SULFUR (WHEN COMBINED WITH NITROGEN & PHOSPHOROUS= TLV.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER FOR 15 MIN

UTES. SKIN: FLUSH WITH WATER.  
INHAL: REMOVE FROM EXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:410F; 210C, COC  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, CO\*2. SEE  
SUPP DATA  
Fire Fighting Procedures:USE H\*2O TO COOL FIRE EXPOSED CONTAINERS SEE  
SUPP DATA  
Unusual Fire/Explosion Hazard:CO,CO\*2,ALDEHYDES,KETONES & COMBUSTION  
PRODUCTS OF NITROGEN & SULFUR MAY FORM IN FIRE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB  
ON SUITABLE MATERIAL & SHOVEL UP.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID EXPOSURES TO HIGH TEMPERATURES &  
WATER CONTAMINATION.  
Other Precautions:FIRE PROCEDURES: H\*2O OR FOAM MAY CAUSE FROTHING. IF  
LEAK OR SPILL IGNITE, USE WATER SPRAY TO DISPERSE VAPORS & PROVIDE  
PROTECTION.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:MFR STATES NONE REQUIRED IF EXPOSURE WITHIN TLV.  
Ventilation:GENERAL VENTILATION RECOMMENDED TO KEEP BELOW TLV.  
Eye Protection:CHEM GOGGLES, FACE SHIELD  
Other Protective Equipment:EXERCISE REASONABLE PERSONAL CLEANLINESS.  
Supplemental Safety and Health  
CONTAINER SIZE: 5 GAL. VISCOSITY: 64.5 CST AT 104F; 40C. OTHER  
INGREDIENTS: METHACRYLATE POLYMER-