View NSN Online: https://aerobasegroup.kr/nsn/8010-00-419-8541

CORONADO PAINT COMPANY, INC. -- PAINT, ACRYLIC EMULSION, WHITE #37875

8010-00-419-8541

Product ID:PAINT, ACRYLIC EMULSION, WHITE #37875

MSDS Date:01/01/1987

FSC:8010

NIIN:00-419-8541

MSDS Number: BDYLL

=== Responsible Party ===

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812 Info Phone Num:90

4-428-6461

Emergency Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

======= Composition/Information on Ingredients ========

Ingred Name:PIGMENT Fraction by Wt: 37.0% ACGIH TLV:NO HAZARD

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 43.5% ACGIH TLV:NO HAZARD

Ingred Name: ACRYLIC RESINS

Fra

========= Hazards Identification =============== Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: NONE SPECIFIED BY MANUFACTURER. Effects of Overexposure: NONE KNOWN Medical Cond Aggravated by Exposure: NONE First Aid:INGESTION: INDUCE VOMITING. GET MEDICAL ATTENTION. EYES: LUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. ============ Fire Fighting Measures ========================= Flash Point:NONE Autoignition Temp: Autoignition Temp Text: NONE Extinguishing Media: NON-FLAMMABLE Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard: MATERIAL MAY SPATTER WHEN TEMPERATURE **EXCEEDS BOILING POINT (212F)** Spill Release Procedures:FLUSH AWAY WITH WATER OR ABSORB ON APPROPRIATE ABSORBANT. Neutralizing Agent:NONE ============ Handling and Storage =========================== Handling and Storage Precautions: DO NOT FREEZE. Other Precautions: NONE ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE NORMALLY REQUIRED Ventilation: LOCAL-ONLY TO AVOID EXCESSIVE INHALATION WHEN SPRAYING. Protective Gloves: NOT REQUIRED Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: FULL WORK C

ction by Wt: 19.5%

ACGIH TLV:NO HAZARD

LOTHING Work Hygienic Practices: WASH THOROUGHLY AFTER PAINTING AND BEFORE EATING OR SMOKING. Supplemental Safety and Health **NONE** ======== Physical/Chemical Properties =========== HCC:N1 Boiling Pt:B.P. Text:212F, 100C Decomp Temp:Decomp Text:>212F,>100C Vapor Pres:16 Vapor Density:0.6 Spec Gravity:1.38 pH:7 Evaporation Rate & Reference: SAME AS WATER Solubility in Water: COMPLETE Appearance and Odor:WHITE PAINT Percent Volatiles by Volume:58.0 ====== Stabi lity and Reactivity Data ======== Stability Indicator/Materials to Avoid:YES **NONE LISTED** Stability Condition to Avoid: AVOID FREEZING TEMPERATURES Hazardous Decomposition Products: NONE LISTED ======= Disposal Considerations ============================= Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the D

epartment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.