

HURON INDUSTRIES, INC. -- MOLYBDENUM DISULFIDE -- 9150-00-424-3224

=====
Product Identification
=====

Product ID:MOLYBDENUM DISULFIDE

MSDS Date:07/17/1990

FSC:9150

NIIN:00-424-3224

Kit Part:Y

MSDS Number: BDYNX

=== Responsible Party ===

Company Name:HURON INDUSTRIES, INC.

Address:2301 16TH STREET

Box:610104

City:PORT HURON

State:MI

ZIP:48061

Country:US

Info Phone Num:313-984-4213

Emergency Phone N

um:313-984-4213

Preparer's Name:JOHN BOUKAMP

CAGE:03432

=== Contractor Identification ===

Company Name:HURON INDUSTRIES INC

Address:2301 16TH ST

Box:610104

City:PORT HURON

State:MI

ZIP:48061-0104

Country:US

Phone:810-984-4213

CAGE:03432

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

Fraction by Wt: 99.0%

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

=====
Hazards Identification

=====
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:REFERENCES AVAILABLE AT THIS TIME DO NOT REPORT ILL HEALTH EFFECTS AS A RESULT OF ACUTE OR CHRONIC OVEREXPOSURE TO MOLYBDENUM DISULFIDE.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SEE HEALTH HAZARDS
Medical Cond Aggravated
by Exposure:CHROMIC RESPIRATORY DISEASE MAY BE AGGRAVATED BY EXPOSURE TO DUST.

=====
First Aid Measures

First Aid:INHALATION:IF A PERSON BREATHE IN A LARGE AMOUNT OF DUST, REMOVE TO FRESH AIR.RESUSCITATE IF NOT BREATHING.GET MEDICAL ATTENTION.EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYE LIDS OPEN.GET MEDICAL ATTENTION.

=====
Fire Fighting Measures

Flash Point:NONE
Ex
tinguishing Media:DRY SAND OR DRY CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
Accidental Release Measures

Spill Release Procedures:CLEANUP BY VACUUM OR WET SWEEPING TO MINIMIZE DUST EXPOSURE.PROVIDE CLEANUP EMPLOYEES WITH RESPIRATORS FOR DUST CONDITIONS.
Neutralizing Agent:NOT APPLICABLE.

=====
Handling and Storage

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE DUST. AVOID MAKING DUST.AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION.

WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATOR.
Ventilation: MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.
Protective Gloves: NATURAL RUBBER
Eye Protection: SAFETY GOGGLES
Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.
Supplemental Safety and Health
THIS IS PART B OF THE LUBRICANT KIT. PART A CONSISTS OF 1000 ML ISOPROPYL ALCOHOL.

=====
===== Physical/Chemical Properties =====

HCC: V6
Decomp Temp: Decomp Text: >599F, >315C
Vapor Pres: 0
Spec Gravity: 4.80
Solubility in Water: INSOLUBLE
Appearance and Odor: BLUE-GRAY TO BLACK CRYSTALLINE POWDER

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
HYDROGEN PEROXIDE
Stability Condition to Avoid: HIGH TEMPERATURES AND OPEN FLAMES
Hazardous Decomposition Products: CARBON MONOXIDE, SULFUR DIOXIDE

=====
===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, S

TATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.