

AMCO CHEMICAL CORP. -- BUTYL CELLOSOLVE -- 6810-00-431-6020

===== Product Identification =====

Product ID:BUTYL CELLOSOLVE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-431-6020

MSDS Number: BDYRH

=== Responsible Party ===

Company Name:AMCO CHEMICAL CORP.

Address:3RD - CYPRS

Box:208

City:OAKLAND

State:CA

ZIP:94607

Country:US

CAGE:97984

=== Contractor Identification ===

Company Name:AMCO CHEMICAL CORP

Addr

ess:3RD - CYPRS

Box:208

City:OAKLAND

State:CA

ZIP:94607

Country:US

Phone:NOT IN BUSINESS! 911008P505A ???

CAGE:97984

===== Composition/Information on Ingredients =====

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 100%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:MODERATELY TOXIC.SKIN:ABSORBS

READILY.INHALED:HIGH VAPOR CONC IRRITAT.EYES:CORNEAL

D

AMAGE.SKIN:IRRIT.

===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H*2O EYES:FLUSH W. H*2O. INGESTED:GIVE 2 GLASSES H*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT ANTHING BY MOUTH.

===== Fire Fighting Measures =====

Flash Point:150F/65.6C TCC

Lower Limits:1.1

Upper Limits:10.6

Extinguishi

ng Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:USE H*2O TO COOL EXPD. CONTRS. USE SCBA & FULL PROT. CLTHG.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP COMBS.(WOOD,PAPER,OIL,ETC.) AWAY FROM SOILLED MATL. DO NOT TOUCH SPILLED MATL. STOP LEAK IF W/O RISK. USE H*2O SPRY TO RED VAPORS. SM SPLS: FLUSH AREA W/FLOODING AMTS OF H*2O. LG SPLS: DIKE FAR A HEAD OF SPILL FOR LATER DI

SPOSAL INTO

APPR CONTRS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING.

Other Precautions:NOTE TO DOCTORS-THERE IS NO SPECIFIC ANTIDOTE.OVEREXPOSURE SHOULD BE TREATED ACCORDING TO SYMPTOMS AND CLINICAL CONDITION.

===== Exposure Controls/Personal Protection =====

Res

piratory Protection:IF EXCED TLV,NIOSH/MSHA APPR SELF-CNTND BRTHG
APP (POS PR MODE)
Ventilation:MECHANICAL (GENERAL) ACCEPTABLE LOCAL EXHAUST IF NEEDED.
Protective Gloves:RUBBER
Eye Protection:MONOGOGGLES
Other Protective Equipment:SAFETY SHOWER & EYE BATH
Supplemental Safety and Health
FP:157F/69.4C TOC.

===== Physical/Chemical Properties =====

HCC:V4
Boiling Pt:B.P. Text:340.2/171.2
Vapor Pres:0.6
Vapor Density:4.1
Spec Gravity:0.90
Evaporation Rate & Refe
rence:0.08(BU AC=1)
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID;MILD ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG ALKALI (E.G. NAOH, NH:4OH,ETC.)
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CO*2, CO, TOXIC OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINE
RATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional adv

ice to verify and
assume responsibility for the suitability of this information to their
particular situation.