

CHEM.SEAL CORP. OF AMERICA -- CS 3204,CLASS B-2,MIL-S-8802 D,PART A -- 8030-00-432-9544

=====  
Product Identification  
=====

Product ID:CS 3204,CLASS B-2,MIL-S-8802 D,PART A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-432-9544

MSDS Number: BDYTD

=== Responsible Party ===

Company Name:CHEM.SEAL CORP. OF AMERICA

Emergency Phone Num:(213)982-1655

CAGE:LO365

=== Contractor Identification ===

Company Name:CHE

M.SEAL CORP. OF AMERICA

CAGE:LO365

Company Name:FLAMEMASTER CORPORATION

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:13422

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 4%.

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:LP-32 LIQUID POLYSULFIDE POLYMER (MFR-THIODOL  
CORP,CHEM

.DIV)

=====  
Hazards Identification  
=====

Effects of Overexposure:AVOID EYE CONTACT OR PROLONGED SKIN CONTACT.

=====  
First Aid Measures  
=====

First Aid:EYE:IMMEDIATELY FLUSH W/WATER FOR 15 MINUTES. CALL MD IF NECESSARY. SKIN:WASH THOROUGHLY W/MILD SOAP & WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:210F CC

Lower Limits:7.

Upper Limits:90.

Extinguishing Media:STANDARD MEDIA,  
CO\*2, ETC.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:MFG SUGGESTS NO PRECAUTIONS NECESSARY; SOLVENT WIPE-TAKING PRECAUTIONS AGAINST FIRE AND INHALATION HAZARDS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID PROLONGED CONTACT.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:MECHAN

ICAL-YES

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GOGGLES REC.

Other Protective Equipment:NONE

Supplemental Safety and Health

PART A OF A 2 PART PRODUCT. MIX RATIO BY WEIGHT IS 100:10(A:B).

KEY1:N1.

=====  
Physical/Chemical Properties  
=====

HCC:N1

Boiling Pt:B.P. Text:450F

Vapor Pres:2.

Vapor Density:3.1

Spec Gravity:1.42

Evaporation Rate & Reference:0.02

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OFF WHITE PASTE, POLYSULFIDE ODOR.

Percent

Volatiles by Volume:4.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
SULFURIC, NITRIC, & HYDROCHLORIC ACIDS.  
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:SANITARY LANDFILL IN ACCORDANCE W/LOCAL, STATE,  
& FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.