

AMERICAN WRITING INK CO.,INC. -- VV-L-800 LUBE OIL -- 9150-00-458-0075

=====
Product Identification
=====

Product ID:VV-L-800 LUBE OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-458-0075

MSDS Number: BDZHT

=== Responsible Party ===

Company Name:AMERICAN WRITING INK CO.,INC.

Address:33 FARNSWORTH ST

City:BOSTON

State:MA

ZIP:02210

Country:US

Info Phone Num:617-482-9167

Emergency Phone Num:617-482-9167

C

AGE:82956

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL

Fraction by Wt: 55.-65%.

OSHA PEL:5 MG/CUM AS OIL MIST

ACGIH TLV:5 MG/CUM AS OIL MIST

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS:75-69-4

RTECS #:PB6125000

Fraction by Wt:

18.-22%.
OSHA PEL:1000 PPM
ACGIH TLV:C, 1000 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)
CAS:75-71-8
RTECS #:PA8200000
Fraction by Wt: 18.-22%.
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:MFR PROVIDES NO INFORMATION
Routes of Entry: Inhalation:YES Skin:YES
Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: NARCOSIS/POSSIBLE CARDIAC
ARRHYTHMIAS. CHRONIC:NO INFORMATION PROVIDED.
Effects of Overexposure:EYES: IRRITATION, REDNESS, TEARING IF CONTACT
OCCURS; SKIN: POSSIBLE DERMATITIS ON PROLONGED/REPEATED EXPOSURE;
INHAL: LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH.
Medical Cond Aggravated by Exposure:MAY AGGRAVATE PRE-EXISTING CARDIAC
PROBLEMS.

===== First
Aid Measures =====

First Aid:EYES: WASH W/ LARGE AMOUNTS OF TEMPERED WATER. IF
IRRITATED-GET MEDICAL ATTN; SKIN: WASH OFF W/ MILD SOAP & WATER. IF
IRRITATION PERSISTS-GET MED ATTN; INHAL:REMOVE TO FRESH AIR. IF
BREATHING HAS CEAS ED, GIVE CPR/O*2 AS SITUATION
DICTATES.INGEST:DONOT INDUCE VOMITING. SEEK IMMEDIATE ATTENTION.
INGESTION WOULD HAVE TO BE DELIBERATE OR ACCIDENTAL SINCE ITEM IS
AN AEROSOL CONFIGURATION.

===== Fire Fighting

Measures =====

Flash Point:N/R FOR AEROSOL

Lower Limits:1.

Upper Limits:7.

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.

Fire Fighting Procedures:USE SELF-CONTAINED BRTHNG APPARATUS IN FIGHTING CHEMICAL FIRES. COOL UNINVOLVED CANS TO PREVENT POSSIBLE BURSTING.

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION MAY PRODUCE TOXIC VAPORS. VAPORS TEND TO COLLECT IN LOW LYING OR POORLY VENTILATED AREAS & DISPLACE AIR.

===== Accidental Releas

e Measures =====

Spill Release Procedures:VENTILATE AREA. SMALL LEAK/SPILL: MOP OR WIPE UP W/ AN INERT ABSORBENT & PLACE IN AN AUTHORIZED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PROTECTIVE CAP IN PLACE WHEN NOT IN USE. STORE IN A COOL, DRY AREA AWAY FROM DIRECT SUNLIGHT. DONOT PUNCTURE OR INCINERATE CAN.

Other Precautions:READ LABEL PRECAUTIONS BEFORE USE. USE ONLY AS DIRECTED. AVOID SPR

AYING ON SKIN OR INTO FACE OR EYES. KEEP FROM REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. USE IN A WELL VENTILATED AREAS. IF ENGINEERING CONTROLS DONOT GIVE AIR CONTAMINANTS BELOW ESTABLISHED PEL'S/TLV'S,A NIOSH/MSHA APPROVED ORGANIC VAPOR/MIST RESPIRATOR SHOULD BE U SED.

Ventilation:AS REQUIRED TO MAINTAIN AIR CONTAMINANTS LEVELS, BELOW ESTABLISHED PEL'S/TLV'S FOR SAFE WORKER ENVIRONME NT.

Protective Gloves:AS REQUIRED FOR TASK AT HAND.

Eye Protection:SAFETY GLASSES/AS REQUIRED FOR TASK.

Other Protective Equipment:AS REQUIRED FOR SAFE WORKER OPERATION.

Work Hygienic Practices:MFR CITES NONE.

Supplemental Safety and Health

ENTRY BASED ON AN OSHA-20 FORMAT OF MSDS RECEIVED 4/89 AFTER PHONE QUERY!

===== Physical/Chemical Properties =====

HCC:V2

Vapor Pres:NOT > 100

Vapor Density:> 1.

Spec Gravity:>1.

Evaporation Rate & Reference:NO REFERENCE

GIVEN

Solubility in Water:NEG

Appearance and Odor:STRAW COLOR, AEROSOL SPRAY. SLIGHT PETROLEUM ODOR.

Percent Volatiles by Volume:40-45

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI OR ALKALINE EARTH METALS. POWDERED AL, ZN, BE, ETC, OXIDIZING MATERIALS, MINERAL ACIDS

Stability Condition to Avoid:OPEN FLAME, IGNITION SOURCES, & GLOWING SURFACES THAT TEND TO DETERIORATE MATERIALS.

Hazardous Decomposition Products:OXI

DES OF CARBON,SMOKE,FUMES

===== Disposal Considerations =====

Waste Disposal Methods:PRODUCT IN AEROSOL CONFIGURATION. DISPOSE OF I/AW ESTABLISHED FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.