

PETERSON HARRY S CO INC -- AEROBOND 2185 PART B -- 8040-00-463-7042

=====
Product Identification
=====

Product ID:AEROBOND 2185 PART B
MSDS Date:01/01/1987
FSC:8040
NIIN:00-463-7042
Kit Part:Y
MSDS Number: BDZLG
==== Responsible Party ====
Company Name:PETERSON HARRY S CO INC
Address:1565 INDUSTRIAL RD
City:SAN CARLOS
State:CA
ZIP:94070-5000
Country:US
Info Phone Num:415-592-8354/415-592-7900
Emerg
ency Phone Num:415-592-8354/415-592-7900
CAGE:FO335
==== Contractor Identification ====
Company Name:ADHESIVE ENGINEERING CO.
Address:1411 INDUSTRIAL CO.
Box:2449
City:SAN CARLOS
State:CA
ZIP:94070
Country:US
CAGE:17433
Company Name:PETERSON HARRY S CO INC
Address:1565 INDUSTRIAL RD
City:SAN CARLOS
State:CA
ZIP:94070-5000
Country:US
Phone:415-592-8354/415-592-7900
CAGE:FO335

=====
Composition/Information on Ingredients
=====

Ingred Name:MODIFIED POLYAMIDE HARDENER

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: MAY BE A SENSITIZER.
Explanation of Carcinogenicity:NONE

==== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS.
INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL
CASES.

=====

=== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:215F
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:AVOID BREATHING SMOKE.
Unusual Fire/Explosion Hazard:NONE

==== Accidental Release Measures =====

Spill Release Procedures:SOAK UP W/ABSORBENT MATERIAL. RESIDUE CAN BE
REMOVED W/SOLVENTS. OBSERVE FIRE HAZARDS.

==== Handling and Storage =====

Handling and Storage Pre
cautions:STORE AT/400F
Spec Gravity:0.936
Solubility in Water:SLIGHT
Appearance and Odor:GREEN LIQUID.
Percent Volatiles by Volume: