View NSN Online: https://aerobasegroup.kr/nsn/3040-00-490-6069

PT COMPONENTS INC, STEARNS DIV -- 8-004-10400 -- 6110-00-490-6069

Product ID:8-004-10400 MSDS Date:01/01/1985 FSC:6110 NIIN:00-490-6069 **MSDS Number: BFBHJ** === Responsible Party === Company Name: PT COMPONENTS INC, STEARNS DIV Address:120 N BROADWAY City:MILWAUKEE State:WI ZIP:53202-6002 Country:US CAGE:05805 === Contractor Identification === **Company Name: PT COMPONEN TS INC STEARNS DIVISION** Address:120 N BROADWAY Box:City:MILWAUKEE State:WI ZIP:53202-6002 Country:US CAGE:05805 Ingred Name: ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE 29CFR 1910.1101) CAS:1332-21-4

RTECS #:CI6475000 OSHA PEL:0.2 FIBERS/CC ACGIH TLV:0.5 FIBERS/CC; A1;89 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Effects of Overexposure: ASBESTOS D

UST IS KNOWN HUMAN CARCINOGEN.ALSO
COUGH, SHORT OF BREATH, WEAKNESS, CYANOSIS, ETC.

======================================
First Aid:SKIN:CONSULT DOCTOR FOR DERMATITIS.EYES:FLUSH WITH WATER FOLLOWED BY TREATMENTS OF OPHTHALMOLOGIST.INHALATION:CONSULT PHYSICIAN AT ONCE.
======================================
Extinguishing Media:EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CNTND BRTHG A PP
======================================
Spill Release Procedures: PICK UP MATERIAL & RETURN TO CONTAINER. IF ANY BROKEN MATRIAL EXISTS, BE CAREFUL TO AVOID DUSTING CONDITIONS. PLACE BROKEN MATERIAL INTO A SEALED CONTAINER. VACUUM OR WET CLEAN ONLY. DO NOT DRY SWEEP.
======================================
Handling and Storage Precautions: AVOID CUTTING OR GRINDING ON ITEM. AVOID ANY DUSTING CONDITIONS. MAINTAIN GOOD HOUSEKEEP ING.
======================================
Respiratory Protection:NIOSH APPROVED DUST MASK AS A MINIMUM.SELF CONT APP FOR DUSTING COND Ventilation:PROVIDE GOOD LOCAL VENTILATION TO KEEP BELOW PEL Protective Gloves:WORKING GLOVES
Eye Protection:SAFETY GLASSES Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.
Supplemental Safety and Health SAFETY DATA DEVELOPED BY DGSC-STF.STORAGE CODE BASED ON FACT THAT ASBESTOS IS

BOUND UP & NOT LOOSE.

HCC:T6

Appearance and Odor: ASBESTOS FIBERS IN BOUND FORM IN FRICTION LINING.

Stability Indicator/Materials to Avoid:YES NONE KNOWN Hazardous Decomposition Products:NONE KNOWN

Waste Disposal Methods:PLACE IN SEALED PLASTIC BAG OR CONTAINER.ULTIMATE DISPOSAL MUST C OMPLY WITH ALL LOAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitab ility of this information to their particular situation.