

AMERON PROTECTIVE COATINGS -- 13538 YELLOW -- 8010-00-515-0559

=====  
Product Identification  
=====

Product ID:13538 YELLOW

MSDS Date:01/01/1987

FSC:8010

NIIN:00-515-0559

MSDS Number: BFBZT

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2

E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL  
CARBINOL (IARC-GROUP 3) \*98-2\*

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 9.0%

Other REC Limits:400 PPM

OSHA PEL:400 PPM

ACGIH TLV:400 PPM

Ingred Name:ALIPHATIC N

APHTHA  
Fraction by Wt: 5.0%

Ingred Name:ISOBUTYL ACETATE  
CAS:110-19-0  
RTECS #:AI4025000  
Fraction by Wt: 7.0%  
Other REC Limits:150 PPM  
OSHA PEL:150 PPM  
ACGIH TLV:713 MG/CUM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE,TOLUOL (IARC CARC- GROUP 3) \*98-2\*  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 8.0%  
Other REC Limits:375 MG/CUM  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE, 2-BUTANONE \*98-2\*  
CAS:78-93-3  
RT  
ECS #:EL6475000  
Fraction by Wt: 18.0%  
Other REC Limits:590 MG/CUM  
OSHA PEL:200 PPM  
ACGIH TLV:590 MG/CUM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====

==== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:30F

Lower Limits:1.1

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE

FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

NP9625000 ISOBUTYL ALCOHOL LT5 P.C.,KK8225000 CELLO.ACETATE LT5 P.C.,SE7555000 VM&P LT5 P.C.,DA070000

0 ETHYL BENZENE LT5P.C.

RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:118-321F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:75.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.