

HY-TEST 303 CORP. -- 810 AQUAGLIDE SILICONE SPRAY (AEROSOL) -- 4220-00-516-3388

=====  
Product Identification  
=====

Product ID:810 AQUAGLIDE SILICONE SPRAY (AEROSOL)

MSDS Date:12/30/1986

FSC:4220

NIIN:00-516-3388

MSDS Number: BFCHK

=== Responsible Party ===

Company Name:HY-TEST 303 CORP.

Address:9 MEADOW RD.

City:RUTHERFORD

State:NJ

ZIP:07070

Info Phone Num:201-933-0300

Emergency Phone Num:201-933-

0300

CAGE:OO156

=== Contractor Identification ===

Company Name:HY-TEST 303 CORP (THRU PARKWAY FABRICATORS)

Address:9 MEADOW RD

Box:City:RUTHERFORD

Phone:201-933-0300

CAGE:OO156

Company Name:HY-TEST INDUSTRIES

Address:99 MORRIS AVE

Box:City:SPRINGFIELD

State:NJ

ZIP:07081

Country:US

Phone:516-593-1434

CAGE:5Y175

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 5%

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE)

(SARA III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 89%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:350 PPM  
ACGIH TLV:350 PPM/450STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:CARBON DIOXIDE  
CAS:124-38-9  
RTECS #:FF6400000  
Fraction by Wt: 3%  
Other REC Limits:ACGIH STEL 30000 PPM  
OSHA PEL:5000 PPM  
ACGIH TLV:5000PPM/30000STEL;93

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion  
:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT IS IRRITATING.  
Effects of Overexposure:EYE:IRRITATION. SKIN:IRRITATION,POSSIBLE  
DERMATITIS. INHALED:RESPIRATORY IRRITATION,HEADACHE,DIZZINESS.  
INGESTED:G/I IRRITATION.  
Medical Cond Aggravated by Exposure:NONE REPORTED. HMIS:PRE-EXISTING  
RESPIRATORY PROBLEMS.

=====  
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:WASH WITH SOAP  
& WATER.  
REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.  
INHALED:REMOVE FROM EXPOSURE. INGESTED:DO NOT INDUCE VOMITING. GET  
MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:N/K(NO FLAME EXT  
Lower Limits:8.0  
Upper Limits:10.5  
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. MAY BURST AT  
TEMPERATURES ABOVE

E 130F/54C.

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB ANY LIQUID ON INERT MATERIAL AND TREAT AS CHLORINATED SOLVENT.

Neutralizing Agent: NONE

===== Handling and Storage =====

Handling and Storage Precautions: STORE AS NON-FLAMMABLE AEROSOL. STORE AT TEMPERATURES BELOW 130F/54C.

Other Precautions: DO NOT USE IN ENCLOSED OR UNVENTILATED AREA.

===== Exposure Controls/Personal Protection

=====

Respiratory Protection: WEAR NIOSH RESPIRATOR FOR ORGANIC VAPORS/MISTS IF EXPOSED ABOVE TLV.

Ventilation: NORMAL ROOM VENTILATION

Protective Gloves: RUBBER OR PLASTIC

Eye Protection: SAFETY GLASSES

Other Protective Equipment: PLASTIC APRON

Work Hygienic Practices: USE NORMAL CHEMICAL HYGIENE PRACTICE.

Supplemental Safety and Health

PRODUCT IS AN AEROSOL CAN OF SILICONE PACKAGED WITH DIVER'S SUIT. THIS P/N IND B IS A PROPELLANT CHANGE AND POSSIBLY A FURTHER FORMULATION CHANGE FROM P/N IND A.

===== Physical/Chemical Properties =====

HCC: V2

Boiling Pt: B.P. Text: 166F/74C

Vapor Pres: 125 MMHG

Vapor Density: 4.6

Spec Gravity: 1.28

Evaporation Rate & Reference: 0.35 BUAC

Solubility in Water: 0.07

Appearance and Odor: CLEAR, COLORLESS, SLIGHTLY OILY LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ALKALIS, REACTIVE METALS

Stability Condition to Avoid: TEMPERAT

URES OVER 130F/54C,FLAME

Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION PLUS  
HYDROGEN CHLORIDE & PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.  
DO NOT PUNCTURE OR INCINERATE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner  
whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.