

PENRECO DIVISION PENNZOIL -- PETROTECT AMBER, CODE 4040 -- 8030-00-526-1604  
===== Product Identification =====

Product ID: PETROTECT AMBER, CODE 4040

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00-526-1604

MSDS Number: BFCLZ

=== Responsible Party ===

Company Name: PENRECO DIVISION PENNZOIL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

=== Contractor Identification ===

Company Name: PENRECO DIVISION, PENNZOTL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

Company Name: PENRECO, DIV OF PENNZOIL CO

Address: 700 MILIAM ST

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Phone: 800-245-3952

CAGE: 86459

===== Composition/Information on Ingredients =====

Ingred Name: STODDARD SOLVENT

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 58.5%

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9293

=====

==== Hazards Identification =====

Effects of Overexposure:EYE: BURNING/IRRIT. SKIN: IRRIT/DERMATITIS.  
INHAL: LOCAL IRRIT,DROW,COMA/PNEUMONIA(SEE SUP DATA)

==== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER FOR AT LEAST 15 MIN.,CALL DOCTOR IMMED.  
SKIN: REMOVE CONTAMINATED CLOTHING WASH EXPOSED AREA W/SOAP &  
WATER,WASH CONTAMINATED CLOTHING BEFORE REUSE. INHAL: REMOVE TO FRESH  
AIR IMMED.A PPLY ARTIFICIAL RESP IF  
NEC (SEE SUP DATA)

==== Fire Fighting Measures =====

Flash Point:100F;38C;TCC  
Lower Limits:1  
Upper Limits:6  
Extinguishing Media:CO\*2,DRY CHEM,FOAM  
Fire Fighting Procedures:USE WATER ONLY TO COOL CANS OF  
FLAM/COMBUSTIBLE MATERIALS.  
Unusual Fire/Explosion Hazard:CONTACT W/ ACID/ACID FUMES/HEATED TO  
DECOMPOSITION WILL EMIT TOXIC FUMES OF SO\*X

==== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE  
VENT,REMOVE IGNITION  
SOURCES,AVOID PROLONGED INHAL OF FUMES & LONG TERM SKIN  
CONTACT,AVOID EYE CONTACT. FLUSH SPILL W/ WATER OR SWEEP UP W/  
ABSORBENT MATERIAL;STORE IN COVERD METALLIC MARKED CANS & DISPOSE  
AS SOON AS POSSIBLE.

==== Handling and Storage =====

Handling and Storage Precautions:FLAM & COMBUSTIBLE LIQUID KEEP AWAY  
FROM SOURCES OF IGNITION. KEEP CANS CLOSED. PROVIDE ADEQUATE VENT.  
USE IN ATMOSPHERE OF INERT GAS INSTEAD OF  
AIR.  
Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. CONTAINER: 55  
GALLON.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROTECTION FOR PARTICULAR  
EXPOSURE OF CONCERN  
Ventilation:RECOMMENDED TO KEEP BELOW TLV.  
Protective Gloves:RUBBER  
Eye Protection:SFTY GOG W/FACE SHIELD.  
Other Protective Equipment:RUBBER PRTECTIVE CLOTHING: BOOTS,APRONS;ETC.  
Supplemental Safety and Health  
SPEC: AM 2 GR4. EFFECTS OF OVEREXPO

SURE: INGEST: LOCAL IRRIT OF MUCOUS

MEMBRANES, MOUTH, THROAT, ESOPHAGUS, STOMACH. EMERGENCY PROCEDURE:

INGEST: DO NOT INDUCE VOMIT CALL DOCTOR IMMED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-325F

Vapor Pres: