View NSN Online: https://aerobasegroup.kr/nsn/8010-00-526-2856 ENMAR -- GRAY 16492;742-624;ENAMEL ALKYD GLOSS -- 8010-00-526-2856 Product ID:GRAY 16492;742-624;ENAMEL ALKYD GLOSS MSDS Date:01/01/1987 FSC:8010 NIIN:00-526-2856 MSDS Number: BFCNS === Responsible Party === Company Name: ENMAR Address: 201 N BERRY ST City:BREA State:CA ZIP:92621-3904 Country:US **CAGE:**OO111 === Contractor Identification === Company Name: AMERON INDUS TRIAL COATINGS DIVISION Address: 201 N BERRY ST Box:City:BREA State:CA ZIP:92621-3904 Country:US Phone:714-529-4597 CAGE:09869 Company Name: ENMAR Address: 201 N BERRY ST Box:City:BREA Phone: (316)-7333-1361 CAGE:00111 ======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 42.3% OSHA PEL:100 PPM

============= Hazards Identification ========================

Effects of Overexposur

e:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE: IRRIT
======================================
First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.
======================================
Flash Point:104F TCC Lower Limits:1.1 Extinguishing Media:SM FIRES:CO *2, DRY CHEM. LG FIRES:POLYMER FOAM PREFERRED
Fire Fighting Procedures:USE SELF-CONTANED BREATHING APPARATUS Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAE, HOT SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS. VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.
=========== Handling and Storage =============
Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ. DO NOT TAKE INTERNALLY. ADD LABEL WARNING. Other Precautions:GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DOT: FLAM LIQUID.
====== Exposure Cont rols/Personal Protection ========
Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUME Protective Gloves:YES
Eye Protection:YES FOR SPLASH Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING
Supplemental Safety and Health VAPOR PRESSURE: 3.2; VAPOR DENSITY: HEAVIER THAN AIR; WT PER GALLON: 9.0 LBS.
========= Physical/Chemical Properties ==========
HCC:F4 Bo

Percent volatiles by volume:60.3
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES
======= Disposal Considerations ===========

Evaporation Rate & Evaporation R

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided w

iling Pt:B.P. Text:311-373F

ith this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.