

ATLAS PAINT & VARNISH CO. -- TT-E-506J,14491 GREEN ALKYD ENAMEL -- 8010-00-527-2625

=====  
Product Identification  
=====

Product ID:TT-E-506J,14491 GREEN ALKYD ENAMEL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2625

MSDS Number: BFCVN

=== Responsible Party ===

Company Name:ATLAS PAINT & VARNISH CO.

Emergency Phone Num:201-373-3300

CAGE:KO008

=== Contractor Identification ===

Company Name:ATLAS PAINT &  
VARNISH CO.

CAGE:KO008

Company Name:ATLAS PAINT AND VARNISH CO

CAGE:84239

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALKYD RESIN

Fraction by Wt: 35.0%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 31.0%

OSHA PEL:100 PPM

Ingred Name:PIGMENTS-TITANIUM DIOXIDE,ALUMINUM SILICATE,CAO\*3  
PHTHALOBLUE,YELLOW OXIDE-SEE SUPP DATA

Fraction by Wt: 33.0%

ACGIH TLV:15 MG/CUM (MFG)

Ingred Name:CALCIUM COBALT DRIE  
RS

Fraction by Wt: 1.0%

ACGIH TLV:500 PPM (MFG)

=====  
Hazards Identification  
=====

Effects of Overexposure:INH OF HIGH CONC W/O PROPER VENTILATION MAY  
CAUSE MILD DEPRESSION TO CONVULSIONS, & UNCONSCIOUSNESS

=====  
First Aid Measures  
=====

First Aid:REMOVE FROM EXPOSURE, CALL MD. REMOVE CONTAMINATED CLOTHING,  
FLUSH AFFECTED AREA W/WATER.

=====  
Fire Fighting Measures  
=====

Flash P

oint:80F TCC

Lower Limits:1.1

Upper Limits:6.0

Extinguishing Media:CO\*2, FOAM, DRY CHEM, WATER FOG

Fire Fighting Procedures:USE AIR-SUPP RESCUE EQUIP, COOL EXPOSED  
CONTAINERS

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMED & DISCARD ABSORBENTS SAFELY.  
REMOVE OPEN IGNITION. DIKE LG SPILLS & PUMP TO WASTE TANK. KEEP  
VENTILATED & AVOID PROLONGED BREATHING OF VAPORS.

===== Handling and Storage =====

=====

Handling and Storage Precautions:AVOID OPEN FLAMES, SPARKS & EXCESSIVE  
HEAT. VENTILATE AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH,MSHA APPROVED

Ventilation:LOCAL EXHAUST, MOST DESIRABEL

Other Protective Equipment:CONVENTIONAL CLOTHES FOR PAINTING

Supplemental Safety and Health

PERCENTAGE FOR PIGMENTS IS FOR ALL THE PIGMENTS, PERCENTAGES FOR  
INDIVIDUAL PIGMENT IS N/A. PIGMENT TLV VASED ON ALL PIGMENTS AND IS  
A

MANUFACTURERS SUGGESTED TLV.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:244-282F

Vapor Pres:8.

Vapor Density:3.9

Spec Gravity:1.2

Evaporation Rate & Reference:1.49 BUAC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN MEDIUM GREEN-BLUE PAINT-MINERAL SPIRIT ODOR

Percent Volatiles by Volume:46

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXYGEN & STRONG OXIDANTS

St

ability Condition to Avoid:OPEN FLAME, HIGH TEMP

Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CO

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professi

onal advice to verify and

assume responsibility for the suitability of this information to their

particular situation.