

CLAYTON CHEMICAL CO -- 176-060 SERIES,CFH FIXER W/HARDNR,PART-A -- 6750-00-528-0473

===== Product Identification =====

Product ID:176-060 SERIES,CFH FIXER W/HARDNR,PART-A

MSDS Date:06/18/1986

FSC:6750

NIIN:00-528-0473

Kit Part:Y

MSDS Number: BFCYV

=== Responsible Party ===

Company Name:CLAYTON CHEMICAL CO

Address:13310 S. FIGUEROA STREET

City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Info Phone Nu

m:213-538-9530

Emergency Phone Num:213-538-9530

Preparer's Name:JOHN B. TAYLOR

CAGE:61803

=== Contractor Identification ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE (WT % NO GIVEN)

CAS:7783-18-8

RTECS #:XN6465000

Ingred Name:SODIUM SULFITE (WT % NOT GIVEN BY MFR)

C

AS:7757-83-7
RTECS #:WE2150000

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF1225000
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BORIC ACID (WT % NOT GIVEN BY MFR)
CAS:10043-35-3
RTECS #:ED4550000

Ingred Name:WATER (% WT NOT GIVEN BY MFR)
CAS:7732-18-5
RTECS #:ZC0110000

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SEVERE EYES IRRITATION &
SKIN DISCOMFORT.
Explanation of Carcinogenicity:NOT LISTED.
Effects of Overexposure:EYES: IRRITATION. SKIN: POSSIBLE IRRITATION ON
PROLONGED CONTACT. INGESTION: PAIN AND UPSET STOMACH.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER. SKIN:WASH WITH SOAP AND
WATER. INGESTION: DRINK WATER AND MI
LK, INDUCE VOMITING AND CALL A
PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:NONE REQUIRED.
Fire Fighting Procedures:NONE REQUIRED.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: MOP UP SPILL ON WASTE TOWELING AND
DISPOSE OF IN A PROPER CONTAINER. LARGE: FLUSH TO SEWER W

ITH PLENTY
OF WATER.
Neutralizing Agent:NONE REQUIRED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY PLACE.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.
Ventilation:MECHANICAL (GENERAL) RECOMMENDED, LOCAL NOT REQUIRED.
Protective Gloves:NONE REQUIRED.
Eye Protection:CHEMICAL SPLASH GOGGLES RECOMMENDED.
Other Protective Equipment:EY
E WASH FACILITY RECOMMENDED.
Work Hygienic Practices:WASH THOROUGHLY AFTER USE.
Supplemental Safety and Health
KEY1:N1; ITEM IS 2 PART KIT; THIS ENTRY DESCRIBES PART A WHICH IS
SERIES 176-060 FIXER (WITH HARDENER), ;HARDENER IS UNDER PNI-B THIS
NSN.

===== Physical/Chemical Properties =====

HCC:C3
Boiling Pt:>100.C, 212.F
Spec Gravity:1.35
pH:5.3
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR,PALE STRAW;SOUR ODOR OF AMMONIA & VINEGAR.

=====

== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS AND STRONG ALKALIS.
Hazardous Decomposition Products:ACIDS: SULFURIC DIOXIDE, ALKALIS,
AMMONIA.

===== Disposal Considerations =====

Waste Disposal Methods:FLUSH TO SEWER WITH PLENTY OF WATER. FOLLOW
FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for us

e by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.