View NSN Online: https://aerobasegroup.kr/nsn/9150-00-529-4308

ANCHOR CHEMICAL COMPANY -- ANCHORLUBE G-771 -- 9150-00-529-4308

Product ID: ANCHORLUBE G-771 MSDS Date:08/05/1991 FSC:9150 NIIN:00-529-4308 **MSDS Number: BFCZL** === Responsible Party === Company Name: ANCHOR CHEMICAL COMPANY Address:777 CANTERBURY RD City:WESTLAKE State:OH ZIP:44145 Country:US Info Phone Num:216-871-1660 Emergency Phone Num:216-871-1660 CAGE:05975 == = Contractor Identification === Company Name: ANCHOR CHEMICAL CO Address:777 CANTERBURY RD Box:City:WESTLAKE State:OH ZIP:44145-1418 Country:US Phone:440-871-1660 CAGE:05975 Ingred Name:TRIETHANOLAMINE CAS:102-71-6 RTECS #:KL9275000 Fraction by Wt: 3-5% Ingred Name: TALL OIL SOAP Fraction by Wt: 20% Ingred Name: MICA - SILICATES (< 1% CRYSTALLINE SILICA) CAS:12001-26-2 RTECS #:VV8760000 Fraction by Wt: 10% **OSHA PEL:20 MPPCF** AC

GIH TLV:3 MG/M3 RDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 3% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:FORMALDEHYDE (SARA III) CAS:50-00-0 RTECS #:LP8925000 Fraction by Wt: 0.1% OSHA PEL:SEE 1910.1048 ACGIH TLV:C 0.3 PPM; A2; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Effects of Overexposure:EYES: WILL IRRIT DUE TO SOAP BASE & T RACE OF FORMALIN.

First Aid:EYES: RINSE W/ COOL WATER FOR 15 MIN.

Flash Point:NONE Extinguishing Media:NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:NOT APPLICABLE. USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: IF POSSIBLE, RETURN MATERIAL TO CONTAINER. WASH DOWN AREA W/ DETERGENT WATER TO REMOVE ANY TRACES OF OILY FILM.

Handling and Storage Precautions: STORE ABOVE 32F & BELOW 75F. MATERIAL WILL FREEZE. VISCOSITY WILL BEGIN TO THIN AT 75F.

Respiratory Protection:MFR RECM NONE. Protective Gloves:NO Eye Protection :SAFETY GLASSES Other Protective Equipment:NONE Supplemental Safety and Health CONTAINER SIZE: 8 OZ BOTTLE. INGREDIENTS: TRI SODIUM PHOSPHATE =1%; TALLOW =10-15%;RED OIL=5-10%; GREEN PIGMENT = TRACE; VEEGUM =5%; WATER= >50%.

Boiling Pt:B.P. Text:225F;107.2C Spec Gravity:1.0365 (H*20=1) Solubility in Water:DISPERSIBLE Appearance and Odor:GREEN SEMI-PASTE W/LEMONY ODOR

Stability Indicator/Materials to Avoid:YES NONE

Waste Disposal Methods:MANUFACTURER STATES NO SPECIAL METHOD NEED.DISPOSAL METHOD MUST BE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr

essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.