

PRATT & LAMBERT - WICHITA DIV. -- 792-310 -- 8010-00-530-6387

=====
Product Identification
=====

Product ID:792-310

MSDS Date:01/01/1985

FSC:8010

NIIN:00-530-6387

MSDS Number: BFDCW

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BEL

LMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 4.94%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS

#:AI4025000
Fraction by Wt: 45.0%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: < 5%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5
000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: < 5%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

==== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC,IRRIT. AIRWAY; SKIN/EYE IRRIT.
HEADACHE,DIZZINESS,COMA,CONFUSION.

==== First Aid Measures =====

First Aid:EYE/SKIN:FLUSH WITH PLENTY OF WATER WHILE REMOVING
CONTAMINATED CLOTHING.I

NHAL:REMOVE TO FRESH AIR.GIVE ARTIF.RESP. IF
NEEDED. CALL MD. IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:44 F, 7 C TCC

Lower Limits:1.3

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL; POLYMER FOAM-LARGE
FIRE

Fire Fighting Procedures:SELF-CONTANED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY
CAUSE EXPLOSION.USE WATER TO COOL CANS.FOR FIRE:FOG NOZZLES

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT
SURFACES, & ELECTRICAL,STATIC,OR FRICTIONAL SPARKS).AVOID BREATHING
VAPORS.VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
AMTS.IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CL
ASS

ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED
WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME
CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPORATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALO

T OF CONTACT

Eye Protection:YES,IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 79-119C. ISOBUTYL ALCOHOL,0.5%,AND XYLENE < 0.5% BY
WEIGHT.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:175-246 F

Evaporation Rate & Reference:< ETHER

Appearance and Odor:YELLOW PAINT

Percent Volatiles by Volume:74.0

===== Stability and Reactivi

ty Data =====

Stability Indicator/Materials to Avoid: YES
Stability Condition to Avoid: FIRES, HEAT, & HOT
SURFACES, SPARKS, ELECTRICAL EQUIP.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IAW LOCAL, STATE, AND FED. REGULATIONS.
INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.