

3M COMPANY -- EC-801 (B2) INDUSTRIAL SEALANT -- 8030-00-537-7925

===== Product Identification =====

Product ID:EC-801 (B2) INDUSTRIAL SEALANT

MSDS Date:01/01/1987

FSC:8030

NIIN:00-537-7925

MSDS Number: BFDHS

=== Responsible Party ===

Company Name:3M COMPANY

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:76381

==

= Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:CARBON BLACK

CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:POLYSULFIDE RUBBER

Ingred Name:PHENOLIC RESIN

Ingred Name:PETROLEUM BASE SOLVENT
Fraction by Wt: 3%

Ingred Name:MAGNESIUM ACETATE
CAS:142-72-3
RTECS #:AI5600000

=====
Hazards Identification
=====

Effects of Overexposure:EYE: IRRIT.SKIN:DEFATTING/DERMATITIS.VAPORS:
HEADACHE,NAUSEA & VOMITING.

=====
First Aid Measures
=====

Fir
st Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN.SKIN:WASH WITH
SOAP AND WATER.INHALATION:REMOVE TO FRESH AIR.

=====
Fire Fighting Measures
=====

Flash Point:>100F/37C
Extinguishing Media:CO2,FOAM,DRY CHEM

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN SPILL.CLEAN UP RESIDUE AND AREA OF
SPILL.PLACE RESIDUE IN CONTAINER.

=====
Handling and Storage
=====

Handli

ng and Storage Precautions:AVOID EYE CONTACT.AVOID PROLONGED BREATHING OF VAPOR AND PROLONG OR REPEATED SKIN CONTACT.KEEP CONTAINER CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

OTHER P/N: SCOTCHSEAL 801(B2) IND SLNT.PART A OF TWO PART EC-801

(B2)IND SLNT KIT. 3M GENERIC ID:62-0801-XXXX-X.ADD INGR:SILICA

PIGMENT & WATER. QTY:3-5/8 FL OZ

=====

===== Physical/Chemical Properties =====

HCC:F4

Spec Gravity:1.36

Solubility in Water:SLIGHT

Appearance and Odor:BLACK,SULFUR ODOR

Percent Volatiles by Volume:3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO2,SULFUR COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:MAY BE DISPOSED OF IN A SANITARY LANDFILL ACCORDING TO LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.