View NSN Online: https://aerobasegroup.kr/nsn/6810-00-546-4343

E.I. DUPONT DE NEMOURS & CO,INC -- FREON T-P 35 -- 6810-00-546-4343

============= Product Identification ===============

Product ID:FREON T-P 35 MSDS Date:01/01/1985

FSC:6810

NIIN:00-546-4343

MSDS Number: BFDTM === Responsible Party ===

Company Name: E.I. DUPONT DE NEMOURS & CO, INC

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE ZIP:19899 Country:US

Info Phone Num:800-441-7515 Emergency Phone Num:800-44

1-7515

CAGE:19898

=== Contractor Identification ===

Company Name: E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE ZIP:19898 Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

Company Name: E.I. DUPONT DE NEMOURS & CO., INC.

Box:1635 CAGE:19898

======= Composition/Information on Ingredients ========

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III)

CAS:76-13-1

RTECS #:KJ4000000 Fraction by Wt: 64.7% OSHA PEL:1000PPM/1 250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1 Ingred Name: NITROMETHANE CAS:75-52-5 RTECS #:PA9800000 Fraction by Wt: 0.3% OSHA PEL:100 PPM ACGIH TLV:100 PPM; 9192 Ingred Name: ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 35% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192 ========== Hazards Identification =============== Effects of Overexposure:LIGHT-HEAD,GIDDY,SHORT OF BRTH,POSSIBL NARCOSIS, POSSIBLE CARDIAC AR RHYTHMIAS AT HIGH CONCENTRATIONS. First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET.DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS. ============ Fire Fighting Measures =========================

Flash Point:120F/49C TOC

Lower Limits:UNK Upper Limits:UNK

Extinguishing Media: ANY AVAILABLE TYPE RECOMMENDED BY MFR.

Fire Fighting Procedu


res:WEAR SELF-CNTND BRTHG APP, IF INVOLVED IN FIRE.

Unusual Fire/Explosion Hazard:ADDITION OF EXCESS WATER(>9%) WILL

EXTRACT ALCOHOL AND MAY FORM A FLAMMABLE, SUPERNATANT LIQUID LAYR.

======== Accidental Release Measures =============

Spill Release Procedures: VENTILATE AREA. ELIMINATE IGNITION SOURCES, ESPECIALLY LOW AREAS WHERE VAPORS MIGHT COLLECT. STOP LEAK. WEAR PROTECTIVE CLOTHES, SCBA. ABSORB SM SPILL WITH SUITABLE ABSORBENT. SHOVEL INTO CONTAINER. LG SPILL: DIKE W



OURCES.CONTACT QUALIFIED

DISPOSAL CONTRACTOR OR MANUFACTURER FOR DISPOSAL METHODS.SEND TO MFR/DISPOSAL CONTRACTOR FOR RECYLE BY DISTILLATION.PACKAGE & DISPOSE IN ACCORDANCE WITH LO CAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.