

EVERSEAL MFG CO INC -- TYPE 1,WHITE -- 8030-00-550-8017

===== Product Identification =====

Product ID:TYPE 1,WHITE

MSDS Date:01/01/1987

FSC:8030

NIIN:00-550-8017

MSDS Number: BFDXX

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-943-1123

Emergency Phone Num:201-943-4986

CAGE:72

988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 15.0%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name

:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 45.0%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:ALKYD RESIN

Fraction by Wt: 2.0%

===== Hazards Identification =====

Effects of Overexposure:DRYING OF SKIN,EYE IRRITATION,EXCESSIVE
INHALATION MAY CAUSE ANESTHESIA,HEADACHE,DIZZINESS,NAUSEA

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH
AIR,APPLY ARTIFICAL RESPIRATION IF
NECESSARY,CALL A PHYSICIAN.SKIN CONTACT:WASH WITH MILD SOAP AND
WATER APPLY A MILD CREME,IN SEVERE CASES CONTACT A
PHYSICIAN,INGESTION: CA LL A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:105F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:EXCLUDE AIR-USE FOAM,CO2,STEAM,DRY CHEMICAL

Fire Fighting Procedures:SUPPLY AIR OR SELF CONTAINED BREATHING
APPARATUS

Unusual Fire/Explosion Hazard:W

ATER MAY BE UNSUITABLE EXCEPT FOR
COOLING EFFECTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OR
CONTAINER.AVOID SPARKS.FIRE OR HOT METAL SURFACES,SMALL QUANTITIES
MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBANT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL & AWAY FROM SOURCE OF
IGNITION. USE WITH ADEQUATE VENTILATION. AVOID PRO

LONGED OR
REPEATED PERSONAL CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH RECOMMENDED RESPIRATOR-DEPENDS ON
CONCENTRATION ABOVE TWA
Ventilation:WHATEVER IS SUFFICIENT TO KEEP WORK ROOM CONCENTRATION
Protective Gloves:IMPERMEABLE
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:APRON, BARRIER CREAM
Supplemental Safety and Health
CHLORINATED LONG CHAIN PARAFFINS 17 PERCENT

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:326-387F
Vapor Pres:5
Vapor Density:4.9
Spec Gravity:1.62
Evaporation Rate & Reference:SLOWER THAN NBUACT
Appearance and Odor:STANDARD PAINT ODOR
Percent Volatiles by Volume:42.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG, OXIDIZING AGENTS
Stability Condition to Avoid:HEAT,SPARK OPEN FLAME,FIRE
Hazardous Decomposition Products:THEMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE AND CO2

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF
IN ACCORDANCE WITH APPLICABLE LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be

accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.