View NSN Online: https://aerobasegroup.kr/nsn/8010-00-582-5382

NATIONAL AEROSOL PRODUCTS(DIST)DEVOE&RAYNOLDS(MFR) -- DR039 FLAT ACRYLIC LACQUER #37038 -- 8010-00-582-5382

Product ID:DR039 FLAT ACRYLIC LACQUER #37038

MSDS Date:01/01/1985

FSC:8010

NIIN:00-582-5382

MSDS Number: BFGGM === Responsible Party ===

Company Name: NATIONAL AEROSOL PRODUCTS (DIST) DEVOE&RAYNOLDS (MFR)

Address:2193 E 14TH ST City:LOS ANGELES

State:CA ZIP:900 21-2843 Country:US CAGE:5N005

=== Contractor Identification ===

Company Name: NATIONAL AEROSOL PRODUCT

Address:2193 E 14TH ST Box:City:LOS ANGELES

State:CA

ZIP:90021-2843 Country:US CAGE:5N005

======= Composition/Information on Ingredients ========

Ingred Name: XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 2.90%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: TOLUENE (SARA III)

C

AS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 24.0% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: METHYL ISOBUTYL KETONE (SARA III) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 21.0% OSHA PEL:100 PPM/75 STEL ACGIH TLV:50 PPM/75 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 19.0% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PP M/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 7.0% OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293

========== Hazards Identification ==============

Effects of Overexposure:INHAL:HEADACHE,NAUSEA,DIZZINESS,SKIN CONTACT:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

First Aid:INHAL:MOVE TO FRESH AIR.SKIN CONTACT-FLU

FOR AT LEAST 15 MIN.CALL PHYSICIAN.
======================================
Flash Point:43 F PMCC Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS TO BE WORN BY FIREFIGHTER Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE
============ Accidental Release Meas ures ====================================
Spill Release Procedures:AVOID BREATHING VAPORS,EXTINGUISH IGNITION SOURCE IN IMMEDIATE AREA.AVOID CONTACT W/LIQUID -MFR RECOMMENDATION
=========== Handling and Storage ============
Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES Other Precautions:CLOSE CONTAINERS AFTER USE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE IN CONFIN ED AREAS. Ventilation:SUFFICIENT LOCAL EXHAUST TO KEEP CONCENTRATION BELOW TLV Protective Gloves:SOLVENT RESIST Other Protective Equipment:NORMAL PROTECTIVE CLOTHING Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:V3 Boiling Pt:B.P. Text:176-343F Spec Gravity:1.04 Evaporation Rate & Evaporation Rat

SH W/LG AMOUNTS OF

========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS,SOFTENS RUBBER Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE
====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM IGNITION SOURCES.-MFR RECOMMENDATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated f or use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.