

SUN REFINING & MARKET CO(MFR), PHIPPS PRDS - DISTR -- SUNVIS 2135-TH(68) --  
9150-00-584-2560

===== Product Identification =====

Product ID:SUNVIS 2135-TH(68)

MSDS Date:01/01/1987

FSC:9150

NIIN:00-584-2560

MSDS Number: BFGJT

=== Responsible Party ===

Company Name:SUN REFINING & MARKET CO(MFR), PHIPPS PRDS - DISTR

Emergency Phone Num:215-447-1852

CAGE:1K762

=== Contractor Identification ===

Company

Name:SUN REFINING & MARKETING CO

Address:1801 MARKET ST

City:PHILADELPHIA

State:PA

ZIP:19103

Country:US

CAGE:1K762

Company Name:SUN REFINING AND MARKETING COMPANY

Address:1801 MARKET ST,TEN PENN CTR

Box:City:PHILADELPHIA

State:PA

ZIP:19103-1699

Country:US

Phone:215-977-6133

CAGE:8X531

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT REFINED HEAVY PARAFFINIC OIL, CAS.# 6474-18-84

Fraction by Wt: UNK

ACGIH TLV:5.0 MG/CUM MFR

Ingred Name:METHACRYLATE POLY

MER  
Fraction by Wt: UNK  
ACGIH TLV:UNK

Ingred Name:RESIN INHIBITOR:PROPRIETARY  
Fraction by Wt: UNK  
ACGIH TLV:UNK

Ingred Name:BUTYLATED HYDROXY TOLUENE  
Fraction by Wt: UNK  
ACGIH TLV:UNK

Ingred Name:PHENYL-ALPHA-NAPHTHYLAMINE  
Fraction by Wt: UNK  
ACGIH TLV:UNK

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE:SLIGHT TRANSIENT IRRIT; SKIN:PRACTICLY  
NON-TOXIC BY SKIN ABSORPTION; INHAL:NONE TO 25MG/CUM-AIR

=====  
First Aid Measu  
res  
=====

First Aid:EYE:FLUSH W/WATER-15 MIN,CALL DOCTOR; SKIN:WASH W/SOAP &  
WATER; INHAL:REMOVE TO FRESH AIR; INGEST:GIVE LIQUIDS & INDUCE  
VOMITING-OBTAIN PHYSICIAN. IF UNCONSCIOUS,DO NOT GIVE LIQUIDS OR  
INDUCE VOMITING . IF SMALL AMTS. ENTER MOUTH,RINSE-OUT THOROUGHLY

=====  
Fire Fighting Measures  
=====

Flash Point:420F/216C COC  
Autoignition Temp:Autoignition Temp Text:700F  
Extinguishing Media:WATER FOG, CHEMICAL FOAM, DRY CHEM  
ICAL, OR CARBON  
DIOXIDE

Fire Fighting Procedures:USE SELF-CNTD BRTHNG APP WHEN FIRE FIGHTNG IN  
CONFIND AREA

Unusual Fire/Explosion Hazard:MFR DOES NOT INDICATE ANY

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CLEAN UP USING AN OIL ABSORBENT.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE PER NFPA CLASS IIIB

=====  
Exposure Controls/Personal Protection  
=====

R

respiratory Protection:NIOSH/MSHA APPRVD RESP DEVICE IAW EXPOSURE OF CONCERN.

Ventilation:LOCAL/MECHANICAL AS REQUIRED TO MAINTAIN AIR QUALITY < TLV.

Protective Gloves:AS REQUIRED- TASK

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED FOR TASK @ HAND

Supplemental Safety and Health

MSDS DATE:6/10/82;INGRED CONTD:SILICONE POLYMER 1001221SP TRACE AMT.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:WIDE RANGE

Vapor Pres:12

Spec

Gravity:0.87

Evaporation Rate & Reference:1000X SLOWER(E.ETH

Solubility in Water:NIL

Appearance and Odor:AMBER COLOR FLUID WITH LITTLE ODOR

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

INCOMPATIBLE W/STRONG OXIDIZERS

Stability Condition to Avoid:EXPOSURE TO HI-TEMP & CONTACT W/OXIDIZERS

Hazardous Decomposition Products:MFR SHOWS NONE;(CARBON DIOXIDE & MONOXIDE, ASPHYXIANTS)

Conditions to

Avoid Polymerization:MATERIAL WILL NOT POLYMERIZE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN COMPLIANCE W/LOCAL, STATE & FEDERAL REGULATIONS WHICH GOVERN DISPOSAL OF OIL OR OIL TYPE MATERIAL OR WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.