

JORDAN PAINT MFG CO -- TT-P-81E, #16187 GRAY OIL ALKYD PAINT EXT -- 8010-00-584-3016

=====
Product Identification
=====

Product ID:TT-P-81E, #16187 GRAY OIL ALKYD PAINT EXT

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3016

MSDS Number: BFGKF

=== Responsible Party ===

Company Name:JORDAN PAINT MFG CO

Address:7250 FRANKLIN ST

City:FOREST PARK

State:IL

ZIP:60130-1162

Country:US

CAGE:28194

=== Contractor

Identification ===

Company Name:JORDAN PAINT MFG CO INC

Address:7250 FRANKLIN ST

Box:City:FOREST PARK

State:IL

ZIP:60130-1162

Country:US

Phone:708-366-8171

CAGE:28194

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPHTHALIC ALKYD RESIN

Fraction by Wt: 24.7%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 13.5%

OSHA PEL:100 PPM

Ingred Name:PENTACHLOROPHENOL (SARA III)

CAS:87-86-5

RTECS #:SM6300000

Fraction

by Wt: 0.5%
OSHA PEL:S, 0.5 MG/M3
ACGIH TLV:S, 0.5 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:TINTING PIGMENT & EXTENDERS
Fraction by Wt: 25.3%

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Fraction by Wt: 10.7%
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Effects of Overexposure:SKIN/EYE IRRIT. AVOID INH OF FUMES.

=====
First Aid Measures
=====

===

First Aid:SKIN: WASH THOROUGHLY W/MILD SOAP & WATER. EYES: IMMEDIATELY FLUSH
W/WATER AT LEAST 15 MIN. CALL MD. INH: MOVE TO FRESH AIR, CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:105F TCC
Extinguishing Media:CO*2, DRY CHEM

=====
Accidental Release Measures
=====

Spill Release Procedures:EXTINGUISH ANY IGNIT SOURCE IN IMMEDIATE AREA.
CLEAN UP W/HI-FLASH SOLVENT TAKING PRECAUTIONS AGAINST FIRE & INH
HAZ. DISPOSE OF
CLEAN-UP CLOTHS & ANY EXCESS FLUIDS IN
TIGHT-FITTING CLOSED METAL CANS.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM SPARKS & EXCESSIVE HEAT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP PROT FOR PARTICULATE EXPOSURE OF
CONCERN
Ventilation:LOCAL EXHAUST IN CONFINED AREAS. MECH, SPARK-PROOF
Protective Gloves:SOLVENT RESISTANT
Eye Protection:FACE MASK OR GOG

GLS
Supplemental Safety and Health
PROD ALSO CONTAINS 4.3% TITANIUM DIOXIDE. TLV OF 5MG/CUM, RESPIRABLE
DUST. 19.2% LINSEED OIL, 1.8% LEAD, CALCIUM, ZINC & MANGANESE
DRIERS.

===== Physical/Chemical Properties =====

HCC:F4
Vapor Density:1
Spec Gravity:1.31
Solubility in Water:NEGLIGIBLE
Appearance and Odor:OPAQUE LIQ, CHARACTERISTIC SOLVENT ODOR
Percent Volatiles by Volume:22.7

===== Stability and Reactivity Data =====

Stability I
Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability
for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.