

DOW CORNING CORPORATION -- DOW CORNING 200 FLUID;200 CST -- 9150-00-584-3134  
===== Product Identification =====

Product ID:DOW CORNING 200 FLUID;200 CST  
MSDS Date:01/01/1987  
FSC:9150  
NIIN:00-584-3134  
MSDS Number: BFGMB  
=== Responsible Party ===  
Company Name:DOW CORNING CORPORATION  
Emergency Phone Num:517-496-5900  
CAGE:5D028

=== Contractor Identification ===  
Company Name:DOW CORNING CORP  
Address:3  
901 S SAGINAW RD  
Box:997  
City:MIDLAND  
State:MI  
ZIP:48686-0997  
Country:US  
Phone:517-496-6000/517-496-6315  
CAGE:5D028  
Company Name:DOW CORNING CORP  
Address:2200 W SALZBURG RD  
Box:City:AUBURN  
State:MI  
ZIP:48611  
Country:US  
Phone:517-496-4388  
CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:SILICONE DC 200 (SILOXANE & SILICONE),CAS#63148-62-9  
RTECS #:JT6485000  
Fraction by Wt: >99%

===== Hazards Identification =====

Effec

ts of Overexposure:EYES:CAUSE TEMPORARY DISCOMFORT;SKIN:  
IRRITATION ON PROLONGED CONTACT;INHAL/INGEST:NO INJURY POSSIBLE

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:6  
00F/315C (O.C)  
Extinguishing Media:WATER,WATERFOG,CO2,DRY CHEMICAL,FOAM.  
Fire Fighting Procedures:SELF-CONT BREATH APP,PROTECTIVE CLOTHING  
Unusual Fire/Explosion Hazard:NONE NOTED

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN  
FOR SALVAGE OR DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL DRY PLACE;USE REASONABLE  
CAR  
E & CAUTION.  
Other Precautions:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE  
VAPORS/ MIST.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE  
VENTILATION  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.  
Supplemental Safety and Health  
MSDS DATE(REVISED) APRIL 11,1986;ITEM IS OF CLASS 4 AND TYPE V OF  
SPEC:VV-D-1078.

=====

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F/149C

Vapor Pres: