

PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA -- 14064 -- 8010-00-584-3149

=====  
Product Identification  
=====

Product ID:14064

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3149

MSDS Number: BFGNC

=== Responsible Party ===

Company Name:PACIFIC AEROSOL,INC.2424 MERCED ST.,SAN LEANDRO CA

Emergency Phone Num:415-351-4860

CAGE:34451

=== Contractor Identification ===

Company Name:AERVOE-PACIFIC CO, I  
NC.

Address:1198 SAWMILL RD

Box:City:GARDNERVILLE

State:NV

ZIP:89410

Country:US

Phone:(702)-782-0100

CAGE:33451

Company Name:PACIFIC AEROSOL, INC.

CAGE:34451

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 19.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 45.0%

OSHA PEL:1

000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SEC-BUTYL ACETATE (SARA III)  
CAS:105-46-4  
RTECS #:AF7380000  
Fraction by Wt: 6.0%  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL  
CAS:111-76-2  
RTECS #:KJ8575000  
Fraction by Wt: 2.0%  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:ISOBUTANE  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 14.0%

=====  
First Aid Measures  
=====

First Aid:FUMES--MOVE AFFECTED TO FRESH AIR, RESTORE BREATHING, GET MEDICAL AID. EYE CONTACT--FLUSH THOROUGHLY WITH WATER, GET MEDICAL AID.

=====  
Fire Fighting Measures  
=====

Flash Point:-2.2F  
Lower Limits:1.0  
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:USE WATER SPRAY TO COOL CLOSED CONTAINERS EXPOSED TO HEAT  
Unusual Fire/Explosion Hazard:KEEP FROM HEAT, SPARKS OR OPEN FLAME.CLOSED CNTAI

CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT OR  
FIRE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION---VENTILATE AREA

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120F. KEEP CONTAINERS AWAY  
FROM HEAT AND OPEN FLAME

Other Precautions:AVOID INHALATION OF SPRAY MIST. DO NOT TAKE  
INTERNALLY

===== Exposure Controls/Personal Protection  
=====

Respiratory Protection:PAINT SPRAY MASK

Ventilation:PROVIDE VENTILATION TO KEEP VAPORS BELOW TLV.

Supplemental Safety and Health

TX2275000 PROPANE 14 PERCENT

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:-10F

Vapor Density:1+

Spec Gravity:0.9

Evaporation Rate & Reference:10

Solubility in Water:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Deco

Composition Products:CARBON MONOXIDE FUMES ON IGNITION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS. DO  
NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be a

ccurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.