

CABOT CORPORATION -- WASPALOY 2590 WELDING WIRE -- 3439-00-586-6676

=====  
Product Identification  
=====

Product ID:WASPALOY 2590 WELDING WIRE

MSDS Date:01/01/1987

FSC:3439

NIIN:00-586-6676

MSDS Number: BFGTL

=== Responsible Party ===

Company Name:CABOT CORPORATION

Emergency Phone Num:(215)9215000

CAGE:CABOT

=== Contractor Identification ===

Company Name:CABOT CORP STELLITE DIV

Address:1020 W PARK A

VE

Box:City:KOKOMO

State:IN

ZIP:46901

Country:US

CAGE:0G043

Company Name:CABOT CORPORATION

Address:COUNTY LINE RD

Box:188

City:BOYERTOWN

State:PA

ZIP:19512

Phone:215-367-2181

CAGE:CABOT

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 58%.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name:CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 19%.

OSHA PEL:1 MG/M3

ACGIH TLV:0.5

MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:COBALT (SARA III)  
CAS:7440-48-4  
RTECS #:GF8750000  
Fraction by Wt: 13.5%  
OSHA PEL:0.1 MG/M3;AS CO  
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:MOLYBDENUM  
CAS:7439-98-7  
RTECS #:QA4680000  
Fraction by Wt: 4.3%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3; 9293

Ingred Name:TITANIUM CAS #7440-32-6  
CAS:7440-32-6  
RTECS #:XR1700000  
Fraction by Wt: 3.0%  
ACGIH TLV:10 MG/CUM

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALATION:IRRITATION,PNEUMONITIS;SKIN  
CONTACT:RASH,ALLERGY.

=====  
===== First Aid Measures =====

First Aid:EYES:FLUSH FOR 15 MIN.SEE A DR.;SKIN:FLUSH W WTR,WASH W SOAP  
& WTR.SEE A DR.;INHALATION:MOVE TO FRESH AIR.SEE A  
DR.;INGESTION:GET MEDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:DRY PWDR,DRY SAND,DRY DOLOMITE,DRY GRAPHITE  
Fire Fighting Procedures:IN A F

IRE WHEN MOLTEN METAL IS PRESENT,USE A  
RESPIRATOR

Unusual Fire/Explosion Hazard:NONE

=====  
Handling and Storage  
=====

Handling and Storage Precautions:NONE

Other Precautions:NONE-MSDS NOT DATED.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH APPVD RESPIRATOR IF TLV IS EXCEEDED

Ventilation:LOCAL EXHAUST

Protective Gloves:GLVS TO AVD.CUT

Eye Protection:USE WHEN MACHNNG,MELTING.

Other Protective Equipme

nt:NONE

Supplemental Safety and Health

OTHER INGRED:IRON 2.0%,TLV 5MG/CUM;SILICON 0.15%,TLV 10,MANGANESE

0.10%,TLV 5;CARBON 0.08%,TLV N/K;ALUMINUM 1.5%,TLV 10;TITANIUM

3.0%,TLV 10;COPPER 0.10%,TLV 0.2;BORON 0.006%,TLV N/K;ZR 0.05%

=====  
Physical/Chemical Properties  
=====

HCC:N1

Appearance and Odor:SOLID-GRAY COLOR

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:

COMPLEX OXIDE COMBINATION OF ALL

ELECTRODE INGREDIENTS.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE OF FUME OR FLUX GRINDING RESIDUE FROM  
THE WORK AREA OR FROM FILTERS IAW EPA OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, war

rants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.